

Index

Symbols

'((((' lookup table element 5-114
'')))' lookup table element 5-114

A

'abrt' lookup table element 5-119
'abyt' lookup table element 5-111
Access Code. *See* password
access control information
 extracting for attribute types 304 to 306
 extracting for dNodes 294 to 296
 extracting for records 298 to 301
 getting 290
 getting for attribute types 301 to 303
 getting for dNodes 291 to 293
 getting for records 296 to 298
access control lists 172 to 173
access controls 165 to 166
 getting 169 to 173
 setting 169 to 173
access privileges 171 to 172
 listing for personal catalogs 242 to 243
access requestors. *See* requestors
Add Enclosure dialog box 3-120 to 3-122
addresses 1-16, 7-10 to 7-17
 direct 7-11 to 7-14
 AppleTalk type 7-12
 telephone type 7-12 to 7-14
 expanding group addresses 3-44
 indirect 7-14 to 7-17
 attribute type 7-15
 queue name type 7-16
 . *See also* message addressing structures
address extensions 2-36, 2-105
address extension types
 'alan' 7-12
 'aphn' 7-13
 'entn' 7-14 to 7-17
 'attr' subtype 7-15
 'qnam' subtype 7-16
 getting 7-113
 setting 7-112
Address field. *See* Recipients field of a mailer
addressing panel 3-6

addressomatic. *See* addressing panel 3-6
address templates A-4
ADSP. *See* AppleTalk Data Stream
'alan' address extension type 7-12
alias
 name 5-86
aliases
 adding to catalogs 264 to 266
 displayed in Catalog-Browsing panel 4-31
 extracting from data structures 2-78
 extracting information about 220 to 221
 extracting information from 204 to 206
 for records, introduced 165
 getting information about 201 to 204, 215 to 219
 resolution for AOCE catalog objects 4-85 to 4-88
 catalog specification structure 4-87
 HFS aliases 4-85
'alng' lookup table element 5-111
alternate user, PowerTalk 9-405
AOCE
 defined xix
 desktop services 1-9 to 1-11
 examples of collaboration applications 1-4 to 1-8
 introduction 1-3 to 1-19
 software, defined xix
 software components 1-8 to 1-14
 software components illustration 1-9
 workflow example 1-7
AOCE attributes. *See* attributes
AOCE catalog records. *See* records
AOCE Catalogs Extension. *See* Catalogs Extension
AOCE catalogs. *See* catalogs
AOCE Collaboration Package 1-11
AOCE data structures
 checking equality of 2-12 to 2-13
 converting between packed and unpacked 2-6
 copying 2-13 to 2-15
 copying versus duplicating 2-15
 duplicating 2-15
 maximum-sized 2-3 to 2-4
 minimum-sized 2-3 to 2-4
 packing 2-5 to 2-10
 unpacking 2-5 to 2-10
 validating 2-10 to 2-12
AOCE identities. *See* identity 166
AOCE interprogram messages. *See* messages
AOCE message. *See* messages
AOCE record attributes. *See* attributes
AOCE records. *See* records

- AOCE strings 2-19 to 2-25
 - allocating non-standard sizes of 2-16
 - character set 2-19
 - checking equality of 2-50
 - converting C strings to AOCE strings 2-46
 - converting Pascal strings to 2-47
 - converting to Pascal strings 2-48
 - copying 2-45
 - header 2-19 to 2-20
 - introduction to 2-19
 - manipulating 2-45 to 2-51
 - minimum-sized 2-4
 - script code 2-19
 - validating 2-51
- AOCE template callback routines 5-196 to 5-246
 - changing the call-for mask 5-198
 - custom views 5-242 to 5-245
 - bounds 5-244
 - reference value 5-242
 - determining a catalog system specification 5-210
 - determining a template's file specification 5-206
 - determining quantity of templates 5-205
 - edit-text views 5-211 to 5-213
 - closing 5-212
 - getting the property number 5-211
 - getting a resource handle 5-207
 - getting information about properties 5-213 to 5-222
 - property-changed flag 5-221
 - property-editable flag 5-222
 - size of a binary property 5-219
 - types 5-215
 - value as a binary block 5-220
 - value as an RString 5-217
 - value as a number 5-216
 - how to call 5-197
 - opening a catalog object 5-211
 - parameter block headers 5-147 to 5-148
 - pop-up menus 5-238 to 5-242
 - adding an item 5-238
 - removing an item 5-240
 - returning text of a menu item 5-241
 - process control 5-199 to 5-200
 - property changed 5-233
 - property dirtied 5-233
 - property type conversions 5-214, 5-223
 - saving a property value 5-234
 - . *See also* routine selectors, AOCE template
 - setting information for properties 5-223 to 5-235
 - parsing an attribute value 5-224
 - setting property-changed flag 5-231
 - setting property-editable flag 5-232
 - type 5-226
 - value as a binary block 5-229
 - value as an RString 5-228
 - value as a number 5-227
 - supporting drops 5-201 to 5-205
 - determining how many objects are being dropped 5-201
 - determining the nature of the destination object 5-202 to 5-205
 - determining the nature of the object being dropped 5-202 to 5-205
 - testing your code resource 5-198
 - unloading templates from memory 5-208
 - updating property values 5-237
 - working with catalog objects 5-209 to 5-211
 - working with sublists 5-235 to 5-238
 - determining number of items in sublist 5-235
 - synchronizing with catalog system 5-237
 - working with templates 5-205 to 5-209
- AOCE template code resource routines 5-148 to 5-196
 - attribute values 5-175 to 5-181
 - adding a new value to a record 5-177
 - adding a new value to a sublist 5-176
 - changing 5-179
 - deleting 5-181
 - call-for mask 5-149
 - conditional views 5-166
 - custom property-type conversions 5-188 to 5-192
 - convert from number 5-191
 - convert from RString 5-192
 - convert to number 5-188
 - convert to RString 5-189
 - custom views and menus 5-192 to 5-196
 - dynamic creation of resources 5-154 to 5-157
 - enabling item in Catalogs menu 5-195
 - example 5-65 to 5-73
 - handling item in Catalogs menu 5-196
 - initializing and removing templates 5-150 to 5-154
 - keypress in information page 5-163
 - main routine prototype 5-148
 - mouse-down event in a custom view 5-194
 - opening an information page 5-158
 - parameter block 5-148
 - parameter block headers 5-145 to 5-147
 - pasting text 5-164
 - processing custom lookup table elements 5-182 to 5-185
 - processing idle-time tasks 5-157 to 5-158
 - property and information-page routines 5-158 to 5-169
 - property changed 5-167
 - property dirtied 5-167
 - reading the routine selector 5-148
 - saving property values 5-168
 - . *See also* AOCE template callback routines
 - . *See also* routine selectors, AOCE template; AOCE template callback routines
 - setting attribute values from properties 5-184
 - setting properties from attribute values 5-182

- setting text length 5-166
- supporting drops 5-169 to 5-174
 - for aspect of destination object 5-173
 - for aspect of dragged object 5-170
- updating custom views 5-193
- updating property values 5-185 to 5-187
- AOCE templates 5-5 to 5-299
 - built-in A-1 to A-4
 - address A-4
 - Group records A-4
 - Key Chain A-4
 - User records A-1 to A-3
 - code resources 5-142 to 5-246
 - data types 5-142 to 5-148
 - rules for writing 5-142
 - exit routine 5-151
 - initializing and removing 5-150 to 5-154
 - names 5-75
 - properties. *See* properties
 - removing and initializing 5-150 to 5-154
 - resource ID values 5-75
 - resources. *See* resources
 - routine selectors. *See* routine selectors, AOCE
 - template
 - sample code 5-30 to 5-73
 - . *See also* aspect templates; file type templates; forwarder templates; information page templates; killer templates
 - template-provided routines. *See* AOCE template
 - code resource routines
 - unloading from memory 5-208
 - writing 5-30 to 5-73
- AOCE toolbox 1-12
- AOCE Utilities 2-3 to 2-139
 - application-defined functions 2-106 to 2-107
 - checking for availability 2-5
 - data structures 2-19 to 2-44
 - functions 2-44 to 2-107
- AOCE utility functions 2-44 to 2-107
 - calling from assembly language 2-44
 - copying functions 2-15
 - duplicating functions 2-15
 - equality functions 2-13
 - packing functions 2-6
 - unpacking functions 2-6
 - validation functions 2-11
- 'aphn' address extension type 7-13
- Apple events
 - opening letters 3-17
 - passing to the Standard Mail Package 3-64
- AppleMail application
 - example of letter 1-5
 - use of 1-7
 - use of standard format 1-11
- Apple Open Collaboration Environment. *See* AOCE
- AppleTalk Data Stream Protocol (ADSP)
 - using for authentication 9-403, 9-409
- AppleTalk Secure Data Stream Protocol (ASDSP). *See* AppleTalk Data Stream Protocol
- AppleTalk Transition Queue (ATQ)
 - using with Authentication Manager 9-407
 - using with Catalog Manager 174
 - using with Interprogram Messaging Manager 7-17
- application-defined routines
 - MyCompletion 9-464
 - MyCompletionRoutine 7-114, 308 to 309
 - MyDrawImage 3-123
 - MyDSSpecStreamer 2-106
 - MyFindPanelBusyProc 4-95
 - MyForEachADAPDirectory function 318
 - MyForEachAttributeAccessControl
 - function 321
 - MyForEachAttrType function 310
 - MyForEachAttrTypeLookup function 313 to 314
 - MyForEachAttrValue function 314 to 315
 - MyForEachDirectory function 311
 - MyForEachDirEnumSpec function 315 to 316
 - MyForEachDNodeAccessControl function 319
 - MyForEachLookupRecordID function 312
 - MyForEachRecordAccessControl function 320
 - MyForEachRecordID function 309 to 310
 - MyFrontWindowCB 3-124
 - MyNotificationProc 9-465
 - MyPanelBusyProc 4-94
 - MyPrepareMailerForDrawing 3-122
 - MyRecipientStreamer 7-115
 - MySendOptionsFilterProc 3-125
 - MyStatusCallback function 6-54 to 6-55
- ASDSP. *See* AppleTalk Data Stream Protocol
- aspect
 - creating an information page from 5-17
 - creating from a record 5-16
 - defined 5-10
 - exit routine 5-154
 - initializing 5-152
 - main
 - defined 5-18
 - for attributes 5-20
 - for records 5-19
 - main view 5-20
 - relation to multiple information pages 5-18
 - relation to records and AOCE templates 5-11
 - saving property values 5-168
 - target selectors 5-144
 - target specifier 5-142 to 5-145
- aspect templates
 - applying to new record or attribute types 5-139, 5-155
 - components of 5-78 to 5-119
 - defined 5-11

- described 5-13 to 5-14
- determining quantity 5-205
- disabling 5-140
- help balloons 5-105
- how they work 5-15 to 5-30
- relation to aspects and records 5-11
- sample 5-33 to 5-36
- . *See also* main aspect templates
- signature resource 5-88
- aspect template target selector 5-145
- ATQ (AppleTalk Transition Queue)
 - using with Authentication Manager 9-407
 - using with Catalog Manager 174
 - using with Interprogram Messaging Manager 7-17
- Attachment field. *See* Enclosures field of a mailer
- attachments. *See* enclosures
- 'attr' address extension subtype 7-15
- attribute creation ID 2-26 to 2-27
 - defined 165
- AttributeCreationID data type 2-26 to 2-27
- Attribute data type 2-39, 2-44
- attribute extension structure 7-26
- attributes
 - adding a new 5-94, 5-176, 5-177
 - AOCE template code resource routines 5-175 to 5-181, 5-182 to 5-185
 - adding a new value to a record 5-177
 - adding a new value to a sublist 5-176
 - changing 5-179
 - deleting 5-181
 - breaking into properties 5-224
 - category, specifying in an aspect template 5-91
 - changing a value 5-179
 - creating from properties. *See* lookup table
 - defined 1-15
 - deleting 5-110
 - deleting a value 5-181
 - dragging values from a sublist 5-102
 - dropping on a record 5-100
 - external category, specifying in an aspect template 5-92
 - from a different record 5-224
 - from outside the catalog system 5-224
 - gender, of record alias 5-94
 - getting information from 6-52 to 6-54
 - information page for 5-23
 - initial value 5-96
 - kind
 - of alias 5-93
 - specifying in an aspect template 5-91
 - main aspect 5-20
 - main aspect and information page template sample code 5-52 to 5-58
 - main aspect template for 5-22
 - multivalued 5-110
 - name 5-86
 - name of new value 5-95
 - new item routine for AOCE templates 5-153
 - parsing into properties 5-224
 - . *See also* lookup table
 - preventing the user from dragging values out of sublists 5-102
 - saving new values 5-27
 - specifying AOCE templates for use with 5-139, 5-155
 - stand-alone 5-6
 - tags 5-77, 5-96, 5-105
- attribute tag AOCE template resource 5-77
- attribute tags. *See* attribute value tags
- attribute-type AOCE template resource 5-75, 5-76, 5-77
- AttributeType data type 2-39, 5-181
- attribute-type indirect addressing 7-15
- attribute types
 - and lookup table 5-105
 - defined 165
 - deleting 284 to 285
 - extracting 288 to 289
 - extracting access control information for 304 to 306
 - extracting attribute values for 280 to 283
 - for AOCE templates 5-75 to 5-77
 - getting 2-94, 285 to 287
 - getting access control information for 301 to 303
 - getting attribute values for 276 to 279
 - managing 266 to 289
 - manipulating 2-94 to 2-95
 - multivalued 5-110
- AttributeValue data type 2-42
- attribute values
 - adding to records 267 to 268
 - changing 270 to 272
 - defined 165
 - deleting from records 269 to 270
 - extracting 280 to 283
 - finding 274 to 276
 - getting 276 to 279
 - managing 266 to 289
 - queue name format 7-16
 - verifying 272 to 273
- attribute value tags
 - and lookup table 5-105
 - AOCE template resource 5-77
 - defined 165
 - for new value 5-96
- AuthAddKey function 9-419
- AuthAddToLocalIdentityQueue function 9-426
- AuthBindSpecificIdentity function 9-435
- AuthChangeKey function 9-420
- AuthChangeLocalIdentity function 9-429
- AuthDecryptCredentials function 9-455 to 9-457
- AuthDeleteKey function 9-422
- AuthDirParamHeader data type 9-414

AuthDirParamHeader type 190
 authenticated-in-catalog requestors 170
 authenticated-in-dNode requestors 170
 authentication
 and Standard Mail Package 3-36
 defined 9-400
 example
 for initiator 9-409
 for Non-ASDSP users 9-409 to 9-410
 for recipient 9-410
 using a proxy 9-410
 using ASDSP 9-408 to 9-409
 generating a challenge 9-451
 generating a reply and counterchallenge 9-452
 indication in message header 7-7
 introduction 1-17
 process described 9-401 to 9-403
 prompting user 4-25 to 4-28
 utilities for non-ASDSP users 9-450 to 9-457
 verifying a reply and replying to a
 counterchallenge 9-454
 authentication identity. *See* identity
 Authentication Manager 9-399 to 9-501
 application-defined functions for 9-464 to 9-466
 data structures for 9-414 to 9-416
 defined 9-406
 functions in 9-416 to 9-464
 calling from assembly language 9-417
 creation ID resolution 9-446 to 9-448
 credentials management 9-439 to 9-446
 key management 9-417 to 9-424
 local identity management 9-424 to 9-434
 managing the PowerTalk Setup catalog 9-457 to
 9-464
 non-ASDSP authentication 9-450 to 9-457
 specific identity management 9-435 to 9-439
 introduction 1-12
 testing for availability 9-407
 testing for version number 9-407
 AuthGetCredentials function 9-439 to 9-441
 AuthGetLocalIdentity function 9-424
 AuthGetSpecificIdentityInfo function 9-438
 AuthGetUTCTime function 9-449
 AuthKey data type 9-416
 AuthKeyType data type 9-416
 AuthLockLocalIdentity function 9-431
 AuthMakeChallenge function 9-451 to 9-452
 AuthMakeProxy function 9-441
 AuthMakeReply function 9-452
 AuthParamBlockPtr data type 9-414
 AuthPasswordToKey function 9-417
 AuthRemoveFromLocalIdentityQueue
 function 9-427
 AuthRemoveLocalIdentity function 9-433
 AuthResolveCreationID function 9-446 to 9-448

AuthSetupLocalIdentity function 9-428
 AuthTradeProxyForCredentials function 9-443
 to 9-446
 AuthUnbindSpecificIdentity function 9-437
 AuthUnlockLocalIdentity function 9-432
 AuthVerifyReply function 9-454
 'awrd' lookup table element 5-111

B

Balloon Help
 in mailers 3-66
 . *See also* help balloons
 'bbit' lookup table element 5-111
 binary property 5-13
 binary property type 5-84
 Bitmap view type 5-128
 blocks, letter
 adding to a letter 3-91 to 3-93
 getting information about 3-104
 reading 3-106
 blocks, message
 current 7-62
 getting type and index 7-96
 nested message 7-59 to 7-61
 nesting 7-56 to 7-59
 reading data 7-98 to 7-101
 starting 7-53 to 7-55
 TOC in message header 7-7
 writing data to 7-61 to 7-65
 block type structure 7-28
 block type values 7-27
 'blok' lookup table element 5-111
 boldface, meaning of xxii
 bounds
 Catalog-Browsing panel 4-30, 4-50
 Find panel 4-64
 information page custom view 5-244
 Box view type 5-128
 browsing AOCE catalogs 4-3, 5-7 to 5-9
 . *See also* Catalog-Browsing panel
 'bsiz' lookup table element 5-115
 'btyp' lookup table element 5-119
 built-in AOCE templates A-1 to A-4
 business cards. *See* information cards
 'bust' file type 4-86
 buttons
 implementing for the Find panel 4-79
 Button view type 5-129, 5-161
 'byte' lookup table element 5-111

C

- callback block headers 5-147 to 5-148
- CallBackDET AOCE template macro 5-197
- callback routines. *See* AOCE template callback routines; application-defined routines
- call block headers 5-145 to 5-147
- call block targeted header 5-146
- call-for mask, AOCE template
 - changing 5-198
 - defined 5-149
- canceling a message 7-67
- capability flags for catalogs. *See* feature flags 162
- Catalog Browser 1-9
- Catalog-Browsing panel
 - adding and removing focus rectangle 4-46
 - bounds 4-30, 4-50
 - changing identity 4-37
 - creating 4-8 to 4-11
 - using function parameters 4-30 to 4-33
 - using resources 4-34 to 4-35
 - defined 4-3
 - displaying contents of a container 4-38
 - disposing 4-50
 - enabling and disabling 4-45
 - events in 4-51 to 4-61
 - determining size of packed record ID of item selected 4-57
 - determining type of item selected 4-55 to 4-56
 - getting packed record ID of item selected 4-58
 - handling 4-11 to 4-18, 4-52 to 4-54
 - opening item selected 4-59 to 4-61
 - getting pathname of item in pop-up menu 4-40 to 4-42
 - help balloons for 4-36
 - hiding 4-43
 - highlighting item that matches string 4-42
 - installing a panel-busy callback function 4-35
 - making visible 4-44
 - moving 4-48
 - panel-busy callback function 4-94
 - resizing 4-49
 - responding to an update event 4-47
 - sample 4-9 to 4-11
 - size of buffer needed for pathname 4-39
 - types of items displayed 4-31
 - types of records displayed 4-31, 4-32
- Catalog-Browsing panel structure 4-20
- catalog discriminators 2-31
 - checking equality of 2-64
 - copying 2-63
 - defined 162
 - manipulating 2-63 to 2-64
- catalog folder. *See* dNodes
- Catalog Manager 161 to 321
 - application-defined functions 308 to 321
 - data types in 190 to 195
 - functions in 196 to 307
 - calling from assembly language 196
 - introduction 1-13
 - testing for availability 174
 - testing for version number 174
- catalog node ID. *See* dNodeID data type 192
- catalog node names
 - determining number in PackedPathName 2-58
- catalog node number. *See* dNode numbers
- catalog node. *See* dNodes
- catalog records. *See* records
- catalogs
 - adding a client key to a catalog 9-419
 - adding aliases to 264 to 266
 - adding to PowerTalk Setup catalog 229 to 234, 9-460
 - addressing 162
 - AOCE template callback routines 5-209 to 5-211
 - browsing 4-3, 5-7 to 5-9
 - changing a client key in a catalog 9-420
 - changing the record ID and password in the PowerTalk Setup catalog 9-461
 - defined 162
 - deleting a client key from a catalog 9-422
 - determining the catalog system specification for an object 5-210
 - example of use 1-5
 - external. *See* external catalogs
 - features, determining 162, 168, 186 to 190, 206 to ??
 - features, determining ?? to 208
 - getting extended information about 212 to 214
 - getting icon information for 210 to 212
 - getting information about 196 to 214
 - getting network information for 209 to 210
 - identifying 163
 - introduction to 1-14, 162 to 167
 - obtaining icons for catalog objects 4-90
 - obtaining root of 2-78
 - opening an object from a template code resource 5-211
 - personal. *See* personal catalogs 162
 - removing from PowerTalk Setup catalog 237 to 239, 9-462
 - See also* external catalogs; personal catalogs; PowerShare catalogs
 - selecting records 4-3
 - structure of 163
 - synchronizing with sublist 5-237
- catalog service access modules. *See* CSAMs
- catalog services specification
 - packing 2-97
- catalog services specifications 2-36 to 2-38
 - checking equality of 2-99
 - converting to stream of bytes 2-105

- defined 2-36
- manipulating 2-95 to 2-106
- obtaining information about 2-103
- packed 2-37
- packed minimum-sized 2-38
- unpacking 2-6 to 2-10
- Catalogs Extension (CE)
 - Catalogs icon 5-6
 - compared with HFS 5-7
 - description 5-5 to 5-9
 - routines used by templates. *See* AOCE template callback routines
 - . *See also* AOCE templates 5-5
- Catalogs icon 5-6
- Catalogs menu
 - adding items 5-137
 - New item, specifying text of 5-94
 - routines to handle custom items 5-192 to 5-196
 - enabling and disabling 5-195
 - responding to user selection 5-196
- catalog system specifier structure. *See* DSSpec data type
- certificate information structure 6-25
- certificate sets 6-6 to 6-7
- certificates. *See* public-key certificates
- CE. *See* Catalogs Extension
- challenge, authentication
 - generating 9-451
 - generating a reply and counterchallenge 9-452
 - obtaining credentials and key 9-440
 - steps in authentication 9-403
 - verifying a reply and replying to a counterchallenge 9-454
- changing the call-for mask 5-198
- character set
 - for AOCE strings 2-19
- Checkbox view type 5-129, 5-161
- client key
 - adding to catalog 9-419
 - changing in catalog 9-420
 - creating from a password 9-417
 - defined 9-400
 - deleting from catalog 9-422
- close-options dialog box 3-60, 3-61
- close-options structure 3-29
- code resources, AOCE templates 5-142 to 5-246
 - data types 5-142 to 5-148
 - example 5-65 to 5-73
 - rules for writing 5-142
 - . *See also* AOCE template callback routines; AOCE template code resource routines; routine selectors, AOCE templates
 - target specifier 5-142 to 5-145
- Collaboration Package 1-11 to 1-12
 - . *See also* Standard Catalog Package; Standard Mail Package
- Collaboration toolbox 1-12 to 1-14
 - . *See also* Authentication Manager; Catalog Manager; IPM Manager
- commands, menu. *See* menu commands
- commands, property. *See* property commands
- CompletionRoutine function 7-114
- completion routines
 - Authentication Manager 9-464
 - IPM Manager 7-41, 7-114
- conditional elements for lookup tables 5-112
- conditional views. *See* views
- connection closed error 7-18
- content enclosures. *See* main enclosures
- content of a letter
 - adding an image to a letter 3-88
 - adding standard interchange format to a letter 3-85 to 3-88
 - reading standard interchange format in a letter 3-98 to 3-102
 - . *See also* image content; native content
- context data structure 6-39
- contexts 6-28 to 6-31
 - creating 6-28 to 6-29
 - disposing 6-29
 - . *See also* queue context
- conventions used in this book xxii
- counterchallenge, authentication
 - generating 9-452
 - replying to 9-454
- cover pages, mailer
 - drawing 3-108
 - preparing 3-107
- creating an aspect from a record 5-16
- creating an information page from an aspect 5-17
- CreationID data type
 - checking equality of 2-52
 - copying 2-52
 - defined 2-26 to 2-27
 - getting null pointer to 2-53
 - getting pointer to PathFinder creation ID 2-54
 - setting to null 2-54
- creation IDs 9-446 to 9-448
 - manipulating 2-51 to 2-55
 - . *See also* attribute creation ID; record creation IDs
- creators
 - determining for letter in the In Tray 3-94
- creator type structure 3-28, 7-27
- credentials
 - decrypting 9-455
 - defined 9-401
 - getting 9-408, 9-439
 - getting a proxy for 9-441
 - management 9-439 to 9-446

- use of 9-403
- using a proxy to obtain 9-443
- cryptographic key. *See* keys, cryptographic
- cryptography 6-4
- 'csam' file type 5-73
- CSAMs (catalog service access modules)
 - introduced 162
- C strings
 - converting to AOCE strings 2-46
- 'cstr' lookup table element 5-111
- current block 7-62
- cursors
 - disabling watch cursor 5-200
 - in mailers 3-66
- custom information page window
 - main aspect and information page template sample
 - code 5-58 to 5-65
 - pop-up menu 5-97
 - resource 5-97
- Custom view type 5-130
- 'cwin' event class 3-67

D

- Data Encryption Standard (DES) 9-400
- date
 - getting information about 6-20
- Date field. *See* Sent field of a mailer
- DefaultButton view type 5-129, 5-161
- delivery notification
 - data structures 7-28 to 7-34
 - delivery result 7-33
 - nondelivery codes 7-29 to 7-30
 - notification types 7-31 to 7-32
 - recipient index 7-33
 - recipient report 7-33
 - report block header 7-33
- DES (Data Encryption Standard) 9-400
- DESKey data type 9-416
- DET. *See* AOCE templates
- DETAAboutToTalkBlock data type 5-200
- DETAddMenuBlock data type 5-238
- 'deta' resource type 5-88
- DETAttributeChangeBlock data type 5-178
- DETAttributeCreationBlock data type 5-175
- DETAttributeDeleteBlock data type 5-180
- DETAttributeNewBlock data type 5-176
- DETBeepBlock data type 5-198
- DETBreakAttributeBlock data type 5-224
- 'detb' resource type 5-96, 5-103
- DETBusyBlock data type 5-200
- DETCallBackBlockHeader data type 5-147

- DETCallBackBlockPropertyHeader data
 - type 5-148
- DETCallBackBlockTargetedHeader data
 - type 5-148
- DETCallBlock data type 5-148
- DETCallBlockHeader data type 5-146
- DETCallBlockPropertyHeader data type 5-146
- DETCallBlockTargetedHeader data type 5-146
- DETChangeCallForsBlock data type 5-198
- DETCloseEditBlock data type 5-212
- DETConvertFromNumberBlock data type 5-190
- DETConvertFromRStringBlock data type 5-191
- DETConvertToNumberBlock data type 5-188
- DETConvertToRStringBlock data type 5-189
- 'detc' resource type 5-84
 - . *See also* code resources
- DETCustomMenuEnabledBlock data type 5-194
- DETCustomMenuSelectedBlock data type 5-195
- DETCustomViewMouseDownBlock data type 5-193
- DETDirttyPropertyBlock data type 5-233
- DETDoPropertyCommandBlock data type 5-245
- DETDoSyncBlock data type 5-186
- DETDropMeQueryBlock data type 5-170
- DETDropQueryBlock data type 5-172
- DETDynamicForwardersBlock data type 5-155
- DETDynamicResourceBlock data type 5-156
- DETExitBlock data type 5-151
- 'detcf' file type 5-12, 5-73
- DETForwarderListItem data type 5-145
- 'detcf' resource type 5-139
- DETFSInfo data type 5-203
- DETGetCommandItemNBlock data type 5-202
- DETGetCommandSelectionCountBlock data
 - type 5-201
- DETGetCustomViewBoundsBlock data type 5-244
- DETGetCustomViewDrawBlock data type 5-192
- DETGetCustomViewUserReferenceBlock data
 - type 5-242
- DETGetDSSpecBlock data type 5-209
- DETGetOpenEditBlock data type 5-211
- DETGetPropertyBinaryBlock data type 5-219
- DETGetPropertyBinarySizeBlock data type 5-218
- DETGetPropertyChangedBlock data type 5-221
- DETGetPropertyEditableBlock data type 5-222
- DETGetPropertyNumberBlock data type 5-216
- DETGetPropertyRStringBlock data type 5-217
- DETGetPropertyTypeBlock data type 5-214
- DETGetResourceBlock data type 5-207
- DETGetTemplateFSSpecBlock data type 5-206
- DETInitBlock data type 5-150
- DETInstanceExitBlock data type 5-154
- DETInstanceIdleBlock data type 5-157
- DETInstanceInitBlock data type 5-152
- 'detc' resource type 5-121
- DETIItemNewBlock data type 5-153

- DETIItem enumeration 5-203
- DETPressBlock data type 5-163
- 'detk' resource type 5-140
- DETPressLengthBlock data type 5-166
- DETPressRStringBlock data type 5-241
- 'detm' resource type 5-104, 5-137
- 'detn' resource type 5-77, 5-103
- DETPressSpecBlock data type 5-210
- DETPressSelfBlock data type 5-158
- DETPressBlock data type 5-164
- DETPressInBlock data type 5-182
- DETPressOutBlock data type 5-184
- 'detp' resource type 5-104
- DETPressCommandBlock data type 5-159
- DETPressDirtiedBlock data type 5-167
- DETPressMenuBlock data type 5-240
- DETPressSyncBlock data type 5-237
- DETPressPropertyBlock data type 5-234
- DETPressSublistCountBlock data type 5-236
- DETPressPropertyBinaryBlock data type 5-229
- DETPressPropertyChangedBlock data type 5-231
- DETPressPropertyEditableBlock data type 5-232
- DETPressPropertyNumberBlock data type 5-227
- DETPressPropertyRStringBlock data type 5-228
- DETPressPropertyTypeBlock data type 5-225
- DETPressShouldSyncBlock data type 5-185
- DETPressSublistCountBlock data type 5-235
- DETPressSelector enumeration 5-144
- DETPressSpecification data type 5-143
- DETPressTemplateCounts data type 5-205
- 'dett' resource type 5-108
 - . See also lookup table
- DETPressUnloadTemplatesBlock data type 5-208
- DETPressValidateSaveBlock data type 5-168
- DETPressViewListChangedBlock data type 5-166
- 'detv' resource type 5-123 to 5-130
 - . See also view lists
- 'detw' resource type 5-97
- 'detx' resource type 5-141
- dialog boxes
 - displayed by AOCE template code resource 5-200
 - and information pages 5-200
- digest data structure 6-44
- digests
 - creating 6-19, 6-43 to 6-44
 - defined 6-5
 - encrypted 6-6
 - generating 6-30
 - size of 6-5, 6-44
 - unencrypted 6-43
- Digital Signature Manager 6-3 to 6-64
 - application-defined functions 6-54 to 6-55
 - data structures for 6-23 to 6-27
 - functions in 6-27 to 6-54
 - introduction 1-12
 - testing for version number 6-11
- digital signatures 6-5 to 6-6
 - adding to a message 7-67
 - checking for 3-83
 - defined 6-3
 - detecting viruses with 6-3
 - icons for 6-26
 - indication in message header 7-7
 - introduction to 6-3 to 6-5
 - relationship to full signatures 6-5 to 6-6
 - . See also full signatures
 - verifying for message 7-102 to 7-103
- DirAbort function 306 to 307
- DirAddADAPDirectory function 229 to 231
- DirAddAlias function 264 to 266
- DirAddAttributeValue function 267 to 268
- DirAddPseudonym function 256 to 258
- DirAddRecord function 247 to 249
- DirChangeAttributeValue function 270 to 272
- DirClosePersonalDirectory function 243 to 244
- DirCreatePersonalDirectory function 240 to 241
- DirDeleteAttributeType function 284 to 285
- DirDeleteAttributeValue function 269 to 270
- DirDeletePseudonym function 258 to 259
- DirDeleteRecord function 249 to 250
- DirDiscriminator
 - checking equality of 2-64
 - copying 2-63
 - data type defined 2-31
- direct addressing 7-11 to 7-14
 - AppleTalk type 7-12
 - telephone type 7-12 to 7-14
- Direct Dialup
 - addresses 7-12 to 7-14
 - defined 7-3
- Directory Manager. See Catalog Manager
- DirectoryName data type 2-22
- DirEnumChoices data type 192
- DirEnumerateAttributeTypesGet function 285 to 287
- DirEnumerateAttributeTypesParse function 288 to 289
- DirEnumerateDirectoriesGet function 196 to 199
- DirEnumerateDirectoriesParse function 199 to 201
- DirEnumerateGet function 215 to 219
- DirEnumerateParse function 220 to 221
- DirEnumeratePseudonymGet function 259 to 262
- DirEnumeratePseudonymParse function 262 to 264
- DirEnumSpec data type 193
- DirFindADAPDirectoryByNetSearch function 232 to 234
- DirFindRecordGet function 201 to 204
- DirFindRecordParse function 204 to 206
- DirFindValue function 274 to 276

- DirGetAttributeAccessControlGet function 301 to 303
- DirGetAttributeAccessControlParse function 304 to 306
- DirGetDirectoryIcon function 210 to 212
- DirGetDirectoryInfo function 168, 206 to 208
- DirGetDNodeAccessControlGet function 291 to 293
- DirGetDNodeAccessControlParse function 294 to 296
- DirGetDNodeInfo function 227 to 228
- DirGetDNodeMetaInfo function 222 to 223
- DirGetExtendedDirectoriesInfo function 182, 212 to 214
- DirGetLocalNetworkSpec function 209 to 210
- DirGetNameAndType function 252 to 253
- DirGetOCESetupRefnum function 239 to 240
- DirGetRecordAccessControlGet function 296 to 298
- DirGetRecordAccessControlParse function 298 to 301
- DirGetRecordMetaInfo function 250 to 252
- DirLookupGet function 276 to 279
- DirLookupParse function 280 to 283
- DirMakePersonalDirectoryRLI function 244 to 246
- DirMapDNodeNumberToPathName function 223 to 225
- DirMapPathNameToDNodeNumber function 225 to 227
- DirMatchWith data type 195
- DirNetSearchADAPDirectoriesGet function 234 to 235
- DirNetSearchADAPDirectoriesParse function 236 to 237
- DirOpenPersonalDirectory function 242 to 243
- DirParamBlock data type 190 to 192
- DirRemoveDirectory function 237 to 239
- DirSetNameAndType function 254 to 255
- 'dirt' file type 4-86
- dirtied property
 - AOCE template callback routine 5-233
 - code resource routine 5-167
- DirVerifyAttributeValue function 272 to 273
- distinguished name 6-9 to 6-11, 6-46
 - getting information about 6-52 to 6-54
- DNodeID data type 192
- dNode list. *See* sublists
- dNode numbers
 - defined 163
 - getting 9-446
 - getting from pathnames 225 to 227
- dNodes
 - adding records to 247 to 249
 - defined 1-14
 - detecting changes in 222 to 223
 - determining number in PackedPathName 2-58
 - displayed in Catalog-Browsing panel 4-31
 - enumerating 193
 - extracting access control information for 294 to 296
 - extracting information from 220 to 221
 - getting access control information for 291 to 293
 - getting dNode number from pathname 225 to 227
 - getting information about 214 to 228
 - getting information about contents of 215 to 219
 - getting pathname information for 223 to 225
 - identifying ability to contain records 227 to 228
 - identifying as foreign nodes 227 to 228
- 'dnod' file type 4-86
- documents
 - digital signatures for. *See* digital signatures 3-41
 - sending as a letter 3-37 to 3-41
- dragging, and AOCE templates. *See* drop operations
- DrawImage function 3-123
- drop operations, and AOCE templates
 - callback routines 5-201 to 5-205
 - determining how many objects are being dropped 5-201
 - determining the nature of the destination object 5-202 to 5-205
 - determining the nature of the object being dropped 5-202 to 5-205
 - categories of records that can be dropped 5-100
 - code resource routines 5-162, 5-169 to 5-174
 - for aspect of destination object 5-173
 - for aspect of dragged object 5-170
 - dropping an attribute on a record 5-100
 - dropping a record on a record 5-99
 - file information 5-203
 - how they work 5-28
 - item types 5-203
 - label for button in dialog box 5-101
 - preventing the user from dragging out attribute values 5-102
 - prompt string 5-101
 - property commands 5-162
 - resources 5-98 to 5-102
 - selection list 5-102
 - types of attribute values that can be dragged out of a sublist 5-102
- 'dsam' file type 5-73
- 'dsig' resource type 6-22, 6-36
- DSSpec data type
 - checking equality of 2-99
 - converting to stream of bytes 2-105
 - defined 2-36
 - obtaining information about 2-103
 - opening a catalog object from a template code resource 5-211
- packed. *See* PackedDSSpec

- packing 2-97
- DSSpec target selector 5-144
- duplicate message delivery 7-18
- dynamic creation of AOCE template resources 5-154 to 5-157

E

- Edit menu
 - mailers and
 - enabling and disabling commands 3-32, 3-69
 - handling commands 3-67
 - handling commands, sample 3-25
 - Undo command 3-33, 3-70
- EditPicture view type 5-130
- edit-text views
 - AOCE template callback routines 5-211 to 5-213
 - closing 5-212
 - getting the property number 5-211
 - closing with default button 5-129
 - in view list 5-128
- EditText view type 5-128
- enclosure descriptor 3-26
- enclosures
 - adding to a mailer 3-119
 - displaying Add Enclosure dialog box 3-120 to 3-122
 - sending with a letter 3-39
- Enclosures field of a mailer
 - adding enclosures to a mailer 3-119, 3-120 to 3-122
 - getting 3-113 to 3-115
- encrypted digests 6-6
 - . *See also* digital signatures
- encryption
 - Data Encryption Standard 9-400
- encryption keys. *See* keys, cryptographic
- entity name extension structure 7-26
- 'entn' address extension type 7-14 to 7-17
 - 'attr' subtype 7-15
 - 'qnam' subtype 7-16
- enumeration choice types 192
- enumeration specifications 193
- 'equa' lookup table element 5-112
- errors
 - from mailer image-drawing routines 3-42
- events
 - Catalog-Browsing panels 4-51 to 4-61
 - determining size of packed record ID of item selected 4-57
 - determining type of item selected 4-55 to 4-56
 - getting packed record ID of item selected 4-58
 - handling 4-11 to 4-18, 4-52 to 4-54
 - opening item selected 4-59 to 4-61
 - Find panels 4-75 to 4-85

- determining size of packed record ID of record selected 4-80
 - determining what action user has taken 4-79 to 4-80
 - getting packed record ID of record selected 4-82
 - handling 4-76 to 4-78
- key-down 3-124
- mailers 3-21 to 3-25, 3-63 to 3-72
 - edit menu commands 3-67 to 3-71
 - having the mailer process events for you 3-63 to 3-67
 - mouse clicks 3-24
 - processing 3-22
 - specifying the active window 3-124
 - update, in mailers 3-72
- exit routines
 - AOCE template 5-151
 - aspect 5-154
- expiration time of credentials 9-455
- extended catalog information, getting 182
- extensions. *See* address extensions
- extension types. *See* address extension types
- external catalogs
 - defined
 - removing from PowerTalk Setup catalog 237 to 239

F

- family, message 7-7, 7-35
- feature flags for catalogs 162, 186 to 190
- 'fext' file type 5-73
- file information, AOCE template drop operations 5-203
- File menu
 - opening a letter 3-95
 - saving a letter 3-80
- 'file' message family type 7-35
- files
 - digital signatures for. *See* digital signatures 6-36
 - sending as letters 3-37 to 3-41
- file system specification
 - determining for an AOCE template file 5-206
- file types
 - 'bust' 4-86
 - 'csam' 5-73
 - 'dett' 5-12, 5-73
 - 'dirt' 4-86
 - 'dnod' 4-86
 - 'dsam' 5-73
 - 'fext' 5-73
 - 'msam' 5-73
 - 'pabt' 4-86
 - 'rcrd' 4-86

- searched by Catalogs Extension 5-15, 5-141
 - used by AOCE templates 5-73
- file type templates 5-12, 5-15
 - components of 5-141
 - disabling 5-140
 - resources 5-141
 - signature resource 5-141
- filters, for message queues
 - changing 7-74
 - general description 7-8
 - queue filter structure 7-35
 - single filter structure 7-34
 - structures 7-34 to 7-35
- Finder
 - AOCE desktop services 1-9 to 1-11
 - Catalog Browser 1-9
- Find panel
 - adding and removing focus rectangle 4-70
 - and Stop button 4-80
 - bounds of elements 4-64
 - changing identity 4-71
 - creating 4-18 to 4-20, 4-61 to 4-65
 - defined 4-3
 - disposing 4-20, 4-75
 - enabling and disabling 4-69
 - events in 4-75 to 4-85
 - determining size of packed record ID of record selected 4-80
 - determining what action user has taken 4-79 to 4-80
 - getting packed record ID of record selected 4-82
 - handling 4-76 to 4-78
 - help balloons for 4-66
 - hiding 4-67
 - implementing buttons and menu items 4-79
 - initial focus rectangle 4-64
 - initiating a search 4-83
 - installing a panel-busy callback function 4-65
 - making visible 4-68
 - moving 4-74
 - panel-busy callback function 4-95
 - responding to an update event 4-72 to 4-73
 - terminating a search 4-84
 - version number 4-5
- FindPanelBusyProc function 4-95
- find panel structure 4-22
- 'find' resource type 4-63
- fixed header information structure 7-38
- focus rectangle
 - adding and removing
 - Catalog-Browsing panel 4-46
 - Find panel 4-70
 - and Catalog-Browsing panel 4-11
 - defined 4-11
 - initial setting for Find panel 4-64

- fonts
 - constants for view lists 5-127
 - converting font numbers in a letter to font names 3-102
 - in letters 3-87
- foreign dNodes
 - identifying as 227 to 228
- forwarder list 5-145
- forwarder templates 5-11, 5-14
 - components of 5-138 to 5-139
 - disabling 5-140
 - resources 5-138 to 5-139
 - signature resource 5-139
- forwarding mail 3-19 to 3-20, 3-49
- friend requestors 170
- From field of a mailer
 - getting 3-111
 - specifying identity 3-117
- FrontWindowCB function 3-124
- full signatures
 - components of 6-5 to 6-7
 - creating 6-8, 6-14 to 6-16, 6-31 to 6-38
 - getting information from 6-19 to 6-22, 6-45 to 6-54
 - verifying 6-6, 6-8, 6-16 to 6-19, 6-38 to 6-40

G

- gender of record kind 5-93
- get functions, using to get access control information 172
- get/parse function pairs 168
 - how to use together 173
 - using with different parameter blocks 174 to 178
 - using with identical parameter blocks 178 to 182
- graphics ports
 - and image-drawing routine 3-124
 - preparing for mailer 3-123
- 'grea' lookup table element 5-113
- Greenwich Mean Time. *See* UTC
- 'greq' lookup table element 5-113
- group addresses
 - expanding 3-44
- Group record templates A-4
- guest, PowerTalk 9-405
- guest requestors 170

H

- header, message
 - authentication field 7-7
 - contents of 7-6

- delivery notification field 7-6
- digital signature field 7-7
- information about 7-37 to 7-39, 7-89 to 7-96
- message family field 7-7
- priority field 7-6
- process hint field 7-7
- recipient location information 7-7
- recipients 7-92 to 7-94
- reply queue field 7-7, 7-95 to 7-96
- sender field 7-7
- table of contents 7-7
- header information structures 7-37 to 7-39
- help balloons
 - aspect templates 5-105
 - for attributes 5-93
 - for Catalog-Browsing panel 4-36
 - for Find panel 4-66
 - main aspect templates 5-93, 5-94
 - for records 5-93
- high-level events
 - passing to the Standard Mail Package 3-64

I

- icon list. *See* sublists
- icon property 5-13
- icons
 - for AOCE templates 5-90
 - for catalog objects, obtaining 4-90
 - for catalog records, obtaining 4-88
 - getting information about 210 to 212
 - for spinning arrows 4-95
- icon suites
 - generic for Standard Catalog Package 4-96
 - standard for digital signatures 6-26
 - standard for Standard Catalog Package 4-97
- icon view type 5-128
- identity 9-403 to 9-405
 - and keys 9-423
 - and Standard Mail Package 3-37
 - defined 166, 9-404
 - for Catalog-Browsing panel 4-37
 - for Find panel 4-71
 - guest 9-405
 - introduction 1-18
 - obtaining 4-8
 - of sender of a letter 3-117
 - prompting for 4-6 to 4-8, 4-25 to 4-28
 - . *See also* local identity; specific identity
- idle processing
 - AOCE templates 5-157 to 5-158
- image block information structure 3-28
- image content

- adding to a letter 3-16, 3-88
- preparing for a letter 3-123
- image files
 - drawing results function 3-42
 - drawing routine 3-39
 - new page function 3-41
 - sending 3-37 to 3-41
- indirect addressing 7-14 to 7-17
 - attribute type 7-15
 - queue name type 7-16
- info page. *See* information page
- information cards 162
 - defined 5-5
 - dragging and dropping 5-28, 5-171
 - use of 1-6
- information page
 - automatically opening for new sublist item 5-96
- callback routines
 - property changed 5-233
 - property dirtied 5-233
- code resource routines 5-158 to 5-169
 - conditional views 5-166
 - keypress routine 5-163
 - maximum text length 5-166
 - overriding normal opening 5-158
 - pasting text 5-164
 - property changed 5-167
 - property dirtied 5-167
 - saving property values 5-168
 - setting default values 5-159
- conditional views
 - defined 5-26
 - implementing 5-131 to 5-136
 - sample 5-40 to 5-43
- creating from an aspect 5-17
- custom views
 - code resource callback routines 5-242 to 5-245
 - code resource routines 5-192 to 5-194
 - defined 5-130
 - getting bounds 5-244
 - getting reference value 5-242
- example 1-6
- opening 5-158
- relation to multiple aspects 5-18
- sublist sample code 5-43 to 5-52
- updating 5-168
- window size 5-97
- information page templates
 - applying to new record or attribute types 5-139, 5-155
 - attribute sample code 5-52 to 5-58
 - components of 5-119 to 5-138
 - custom window resource 5-97
 - custom window sample code 5-58 to 5-65
 - defined 5-11

- described 5-14
- determining quantity 5-205
- disabling 5-140
- for attribute in sublist 5-23
- for record in sublist 5-24
- how they work 5-15 to 5-30
- naming information page 5-137
- page-selection pop-up menu 5-97
- record sample code 5-36 to 5-40
- relation to aspects and records 5-11
- resources 5-120 to 5-138
- signature resource 5-121 to 5-123
- specifying the main view aspect 5-136
- sublist 5-136
- view list 5-123 to 5-131
- view types 5-127 to 5-130
- information page template target selector 5-145
- initiator of authentication process 9-409
- intermediary
 - defined 9-406
 - obtaining proxy 9-442
 - obtaining record ID 9-455
- interprogram messages. *See* messages
- interprogram messaging addresses. *See* addresses
- Interprogram Messaging Manager 7-3 to 7-158
 - application-defined functions for 7-114 to 7-116
 - completion routine 7-114
 - data structures for 7-24 to 7-41
 - delivery notification 7-28 to 7-34
 - message addressing structures 7-24 to 7-26
 - message and block types 7-26 to 7-28
 - functions in 7-42 to 7-114
 - calling asynchronously or synchronously 7-41
 - calling from assembly language 7-43, 7-107
 - completion routines 7-41
 - creating a new message 7-43 to 7-68
 - deleting messages 7-105 to 7-107
 - listing and reading messages 7-80 to 7-105
 - managing message queues 7-68 to 7-80
 - utilities 7-107 to 7-114
 - introduction 1-13
 - relationship to Standard Mail Package 7-3
 - services provided 7-4
 - testing for availability 7-17
 - testing for version number 7-17, 7-38
- Interprogram Messaging parameter block header 7-40
- In Tray
 - getting information about a letter 3-93
 - obtaining letter descriptor of next item to open 3-97
- I/O tasks
 - advantage of packed structures for 2-5
- IPMAddRecipient function 7-50 to 7-51
- IPMAddReplyQueue function 7-52
- IPM addresses. *See* addresses
- IPMBlockType data type 7-28
- IPMChangeQueueFilter function 7-74
- IPMCloseContext function 7-77
- IPMCloseMsg function 7-104 to 7-105
- IPMCloseQueue function 7-76
- IPMCreateQueue function 7-69 to 7-70
- IPMDeleteMsgRange function 7-106 to 7-107
- IPMDeleteQueue function 7-78
- IPMEndMsg function 7-65 to 7-68
- IPMEntityNameExtension data type 7-26
- IPMEntnAttributeExtension data type 7-26
- IPMEntnQueueExtension data type 7-26
- IPMEnumerateQueue function 7-80 to 7-82
- IPMFilter data type 7-35
- IPMFixedHdrInfo data type 7-38
- IPMGetBlkIndex function 7-96
- IPMGetMsgInfo function 7-87
- IPM Manager. *See* Interprogram Messaging Manager
- IPMMsgID data type 7-32
- IPMMsgInfo data type 7-36
- IPMMsgType data type 7-28
- IPMNestMsg function 7-59 to 7-61
- IPMNewBlock function 7-53 to 7-55
- IPMNewHFMsg function 7-47 to 7-50
- IPMNewMsg function 7-43 to 7-47
- IPMNewNestedMsgBlock function 7-56 to 7-59
- IPMNotificationType data type 7-31
- IPMOpenBlockAsMsg function 7-86 to 7-87
- IPMOpenContext function 7-70
- IPMOpenHFMsg function 7-84
- IPMOpenMsg function 7-82 to 7-84
- IPMOpenQueue function 7-72 to 7-74
- IPMReadHeader function 7-89 to 7-92
- IPMReadMsg function 7-98 to 7-101
- IPMReadRecipient function 7-92 to 7-94
- IPMReadReplyQueue function 7-95 to 7-96
- IPMReportBlockHeader data type 7-33
- IPMSender data type 7-40
- IPMSingleFilter data type 7-34
- IPMTOC data type 7-37
- IPMVerifySignature function 7-102 to 7-103
- IPMWriteMsg function 7-61 to 7-65
- isAlias lookup-table flag 5-109
- isRecordRef lookup-table flag 5-109
- issue time of credentials 9-455
- item types for drop operations 5-203

J

- justified text
 - in AOCE templates 5-127

K

-
- kDETAAddNewItem metaproperty 5-87
 - kDETAAspectAliasGender resource ID offset 5-94
 - kDETAAspectAliasKind resource ID offset 5-93
 - kDETAAspectAliasWhatIs resource ID offset 5-94
 - kDETAAspectAttrDragIn resource ID offset 5-100
 - kDETAAspectBalloons resource ID offset 5-105
 - kDETAAspectCategory resource ID offset 5-91
 - kDETAAspectDragInString resource ID offset 5-101
 - kDETAAspectDragInSummary resource ID offset 5-102
 - kDETAAspectDragInVerb resource ID offset 5-101
 - kDETAAspectDragOut resource ID offset 5-102
 - kDETAAspectExternalCategory resource ID offset 5-92
 - kDETAAspectGender resource ID offset 5-93
 - kDETAAspectInfoPageCustomWindow resource ID offset 5-97
 - kDETAAspectKind resource ID offset 5-91
 - kDETAAspectLookup resource ID offset 5-108 to 5-119
 - kDETAAspectMainBitmap resource ID offset 5-90
 - kDETAAspectName property 5-86
 - kDETAAspectName resource ID offset 5-95
 - kDETAAspectNewEntryName resource ID offset 5-95
 - kDETAAspectNewMenuName resource ID offset 5-94
 - kDETAAspectNewValue resource ID offset 5-96
 - kDETAAspectRecordCatDragIn resource ID offset 5-99
 - kDETAAspectRecordDragIn resource ID offset 5-99
 - kDETAAspectReverseSort resource ID offset 5-104
 - kDETAAspectSublistOpenOnNew metaproperty 5-87, 5-96
 - kDETAAspectSublistOpenOnNew resource ID offset 5-96
 - kDETAAspectTemplateName metaproperty 5-86
 - kDETAAspectTemplate target selector 5-145
 - kDETAAspectViewMenu resource ID offset 5-103
 - kDETAAspectWhatIs resource ID offset 5-93
 - kDETAAttributeAccessMask metaproperty 5-87
 - kDETAAttributeType resource ID offset 5-76, 5-77
 - kDETAAttributeValueTag resource ID offset 5-77
 - kDETCmdAboutToTalk template callback routine 5-200
 - kDETCmdAddMenu template callback routine 5-238
 - kDETCmdAttributeChange template-provided routine 5-178
 - kDETCmdAttributeCreation template-provided routine 5-175
 - kDETCmdAttributeDelete template-provided routine 5-180
 - kDETCmdAttributeNew template-provided routine 5-176
 - kDETCmdBeep template callback routine 5-198
 - kDETCmdBreakAttribute template callback routine 5-224
 - kDETCmdBusy template callback routine 5-200
 - kDETCmdChangeCallFors template callback routine 5-198
 - kDETCmdCloseEdit template callback routine 5-212
 - kDETCmdConvertFromNumber template-provided routine 5-190
 - kDETCmdConvertFromRString template-provided routine 5-191
 - kDETCmdConvertToNumber template-provided routine 5-188
 - kDETCmdConvertToRString template-provided routine 5-189
 - kDETCmdCustomMenuEnabled template-provided routine 5-194
 - kDETCmdCustomMenuSelected template-provided routine 5-195
 - kDETCmdCustomViewDraw template-provided routine 5-192
 - kDETCmdCustomViewMouseDown template-provided routine 5-193
 - kDETCmdDirtyProperty template callback routine 5-233
 - kDETCmdDoPropertyCommand template callback routine 5-245
 - kDETCmdDoSync template-provided routine 5-186
 - kDETCmdDropMeQuery template-provided routine 5-170
 - kDETCmdDropQuery template-provided routine 5-172
 - kDETCmdDynamicForwarders template-provided routine 5-155
 - kDETCmdDynamicResource template-provided routine 5-156
 - kDETCmdExit template-provided routine 5-151
 - kDETCmdGetCommandItemN template callback routine 5-202 to 5-205
 - kDETCmdGetCommandSelectionCount template callback routine 5-201
 - kDETCmdGetCustomViewBounds template callback routine 5-244
 - kDETCmdGetCustomViewUserReference template callback routine 5-242
 - kDETCmdGetDSSpec template callback routine 5-209
 - kDETCmdGetOpenEdit template callback routine 5-211
 - kDETCmdGetPropertyBinarySize template callback routine 5-218
 - kDETCmdGetPropertyBinary template callback routine 5-219
 - kDETCmdGetPropertyChanged template callback routine 5-221
 - kDETCmdGetPropertyEditable template callback routine 5-222
 - kDETCmdGetPropertyNumber template callback routine 5-216

- kDETCmdGetPropertyRString template callback routine 5-217
- kDETCmdGetPropertyType template callback routine 5-214
- kDETCmdGetResource template callback routine 5-207
- kDETCmdGetTemplateFSSpec template callback routine 5-206
- kDETCmdIdle template-provided routine 5-157
- kDETCmdInit template-provided routine 5-150
- kDETCmdInstanceExit template-provided routine 5-154
- kDETCmdInstanceInit template-provided routine 5-152
- kDETCmdItemNew template-provided routine 5-153
- kDETCmdKeyPress template-provided routine 5-163
- kDETCmdMaximumTextLength template-provided routine 5-166
- kDETCmdMenuItemRString template callback routine 5-241
- kDETCmdOpenDSSpec template callback routine 5-210
- kDETCmdOpenSelf template-provided routine 5-158
- kDETCmdPaste template-provided routine 5-164
- kDETCmdPatternIn template-provided routine 5-182
- kDETCmdPatternOut template-provided routine 5-184
- kDETCmdPropertyCommand template-provided routine 5-159
- kDETCmdPropertyDirtyed template-provided routine 5-167
- kDETCmdRemoveMenu template callback routine 5-240
- kDETCmdRequestSync template callback routine 5-237
- kDETCmdSaveProperty template callback routine 5-234
- kDETCmdSelectedSublistCount template callback routine 5-236
- kDETCmdSetPropertyBinary template callback routine 5-229
- kDETCmdSetPropertyChanged template callback routine 5-231
- kDETCmdSetPropertyEditable template callback routine 5-232
- kDETCmdSetPropertyNumber template callback routine 5-227
- kDETCmdSetPropertyRString template callback routine 5-228
- kDETCmdSetPropertyType template callback routine 5-225
- kDETCmdShouldSync template-provided routine 5-185
- kDETCmdSublistCount template callback routine 5-235
- kDETCmdTemplateCounts template callback routine 5-205
- kDETCmdUnloadTemplates template callback routine 5-208
- kDETCmdValidateSave template-provided routine 5-168
- kDETCmdViewListChanged template-provided routine 5-166
- kDETDNodeAccessMask metaproperty 5-87
- kDETDSSpec target selector 5-144
- kDETForwarderTemplateName resource ID offset 5-139
- kDETInfoPageMainViewAspect resource ID offset 5-136
- kDETInfoPageMenuEntries resource ID offset 5-137
- kDETInfoPageName resource ID offset 5-137
- kDETInfoPageNumber metaproperty 5-86
- kDETInfoPageTemplateName metaproperty 5-87
- kDETInfoPageTemplate target selector 5-145
- kDETKillerName resource ID offset 5-140
- kDETOpenSelectedItems metaproperty 5-87
- kDETParent target selector 5-144
- kDETPastFirstLookup metaproperty 5-86, 5-168
- kDETPrimaryAddMask metaproperty 5-87
- kDETPrimaryChangeMask metaproperty 5-87
- kDETPrimaryChangePrivsMask metaproperty 5-87
- kDETPrimaryDeleteMask metaproperty 5-87
- kDETPrimaryMaskByBit metaproperty 5-87
- kDETPrimaryRenameMask metaproperty 5-87
- kDETPrimarySeeMask metaproperty 5-87
- kDETPrKind metaproperty 5-86
- kDETPrName metaproperty 5-86, 5-95
- kDETPrTypeBinary property type 5-84
- kDETPrTypeNumber property type 5-84
- kDETPrTypeString property type 5-84
- kDETRecordAccessMask metaproperty 5-87
- kDETRecordType resource ID offset 5-76
- kDETRemoveSelectedItems metaproperty 5-87
- kDETSelctedSublistItem target selector 5-144
- kDETSelfOtherAspect target selector 5-144
- kDETSelf target selector 5-144
- kDETSublistItem target selector 5-144
- kDETTemplateName resource ID offset 5-75
- Key Chain
 - disabling 9-434
 - introduction 1-18
 - locking 9-431
 - . *See also* local identity 9-431
 - unlocking 9-433
- Key Chain Access Code 4-6
- Key Chain templates A-4
- key-down events
 - determining if a mailer is the target 3-31
 - in information page 5-163
 - specifying if a mailer is the target 3-54
 - specifying the active window 3-124
- keypress

- AOCE template code resource routine 5-163
- keys, cryptographic
 - adding a client key to a catalog 9-419
 - binding to a specific identity 9-435
 - changing a client key in a catalog 9-420
 - client 9-400
 - decryption 6-4
 - deleting a client key from a catalog 9-422
 - encryption 6-4
 - management 9-417 to 9-424
 - obtaining for challenge 9-440
 - session 9-400, 9-455
 - translating a password into a client key 9-417
 - unbinding from a specific identity 9-437
- key structure 9-416
- killer templates 5-12, 5-15
 - components of 5-140 to 5-141
 - resources 5-140 to 5-141
 - signature resource 5-140
- kind
 - attribute 5-91
 - attribute alias 5-93
 - record
 - gender 5-93
 - specifying 5-91
 - record alias
 - gender 5-94
 - specifying 5-93
- kIPMFAMILYUnspecified message family type 7-35
- kIPMFAMILYWildcard message family type 7-35
- kMailFAMILYFile message family type 7-35
- kMailFAMILY message family type 7-35

L

- 'leeq' lookup table element 5-113
- 'less' lookup table element 5-112
- letter descriptor 3-27
- LetterDescriptor data type 3-27
- letter information structure 3-27
- letter parameter block 3-29
- letters
 - adding a block 3-91 to 3-93
 - adding a main enclosure 3-90
 - adding content 3-13
 - adding image content 3-16, 3-88
 - adding native-format content 3-14
 - adding standard-interchange-format content 3-15, 3-85 to 3-88
 - Apple event handler 3-17
 - blocks 3-7
 - checking for digital signatures 3-83
 - close-options dialog box 3-60

- closing 3-20, 3-21, 3-59 to 3-63
- content changed 3-76
- drawing image content 3-123
- enclosures 3-7, 3-39
- expanding group addresses 3-44
- extending the send-options dialog box 3-125
- formats of 3-7
- forwarding 3-19 to 3-20, 3-49
- getting information about a letter in the In Tray 3-93
- identity of sender 3-117
- image-drawing results function 3-42
- image-drawing routine 3-39
- main enclosure 3-7
- nested 3-8, 7-5
- new page function 3-41
- obtaining letter descriptor of next letter to open 3-97
- opening 3-18, 3-94 to 3-96
- reading 3-93 to 3-107
 - blocks 3-106
 - converting font numbers to font names 3-102
 - getting information about blocks 3-104
 - getting main enclosure 3-103
 - standard interchange format content 3-98 to 3-102
- replying to 3-19 to 3-20, 3-51
- saving
 - beginning 3-77 to 3-80
 - ending 3-80
- . See also mail; messages
- send formats 3-34
- sending 3-37 to 3-41, 3-72 to 3-93
 - beginning 3-81 to 3-83
 - ending 3-84
 - send-options dialog box 3-73 to 3-76
- send options 3-34
- standard interchange format 3-7
- structure 3-7
- tags 3-58
- LetterSpec data type 3-35, 5-204
- letter-specification structure 3-35, 5-204
- local identity
 - changing password 9-429
 - defined 4-6, 166, 9-404
 - getting 9-424
 - introduction 1-18
 - locking 9-404, 9-431
 - management 9-424 to 9-434
 - prompting for 4-25 to 4-28
 - removing 9-433
 - . See also notification queue, local identity
 - setting up 9-428
 - unlocking 9-404, 9-432
- LocalRecordID data type
 - 2-27 to 2-28
 - checking equality of 2-81
 - copying 2-80

- creating 2-79
- manipulating 2-79 to 2-82
- local record identifiers
 - checking equality of 2-81
 - copying 2-80
 - creating 2-79
 - data type defined 2-27 to 2-28
 - manipulating 2-79 to 2-82
- 'long' lookup table element 5-111
- lookup table 5-105 to 5-119
 - block and size elements examples 5-116 to 5-118
 - code resource routines 5-182 to 5-185
 - converting property values to attribute values 5-184
 - parsing attribute values 5-182
 - defined 5-25
 - described 5-106
 - elements that repeat patterns 5-115
 - flags 5-109 to 5-110
 - format of 5-107
 - mechanism 5-25
 - overriding default property types 5-119
 - pattern elements 5-111 to 5-119
 - basic 5-111
 - block 5-113 to 5-118
 - cancel processing 5-119
 - conditional 5-112
 - custom 5-118
 - property type 5-119
 - size 5-115 to 5-118
 - providing your own elements 5-118
 - resource 5-108 to 5-110
- 'lsiz' lookup table element 5-115

M

mail

- displaying the send-options dialog box 3-11
- forwarding 3-19 to 3-20
- obtaining letter descriptor of next item in In Tray 3-97
- opening 3-18, 3-94 to 3-96
- reading 3-93 to 3-107
- receiving 3-17 to 3-19
 - Apple event handler 3-17
- replying to 3-19 to 3-20, 3-51
- saving
 - beginning 3-77 to 3-80
 - ending 3-80
- . *See also* letters; messages
- sending 3-11 to 3-16, 3-72 to 3-93
 - adding image content 3-16
 - adding letter content 3-13

- adding native-format content 3-14
- adding standard-interchange-format content 3-15
- beginning 3-81 to 3-83
- ending 3-84
- extending the send-options dialog box 3-125
- main routine 3-12
- send-options dialog box 3-73 to 3-76
- mailbox, letter tags 3-58
- mailers
 - adding to a window 3-9 to 3-11, 3-46
 - Balloon Help 3-66
 - basic support 3-7
 - closing 3-59 to 3-63
 - close-options dialog box 3-60
 - deallocating the mailer 3-61
 - determining if possible 3-59
 - cursor 3-66
 - defined 3-4
 - determining if a mailer can be forwarded 3-31, 3-50
 - determining if a mailer is the target 3-31
 - determining whether the mailer has been changed 3-31
 - disposing 3-61
 - drawing 3-72
 - drawing cover pages 3-108
 - drawing-preparation function 3-122
- Edit menu
 - determining which commands to enable 3-69
 - handling commands 3-25, 3-67
 - Undo command 3-70
- event handling 3-63 to 3-67
- expanding and contracting 3-56, 3-66
- forwarding 3-49
- full support 3-7
- functions 3-45 to 3-122
- getting and setting contents 3-110 to 3-122
- getting information
 - determining buffer size 3-110
 - From, Subject, and Sent fields 3-111
 - Recipients and Enclosure fields 3-113 to 3-115
- handling mailer events 3-21 to 3-25, 3-63 to 3-72
 - mouse clicks 3-24
 - processing events 3-22
- initializing mailer functions 3-46
- initially expanded or contracted 3-47, 3-52
- introduction 3-4 to 3-6
- moving 3-57
- position 3-47
- preparing cover pages 3-107
- printing and imaging 3-107 to 3-109
- replying to 3-51
- sample 3-9 to 3-11
- setting information
 - Enclosures field 3-120 to 3-122
 - Enclosures field of a mailer 3-119

- From field 3-117
 - Recipients field 3-118
 - Subject field 3-116
- specifying target of key-down events 3-54
- standard dimensions 3-48
- target components 3-32
- updating 3-72
- using Tab key to move among fields 3-53 to 3-56
- mailer set 3-4
- mailer-state structure 3-30 to 3-34
- Mail menu
 - adding a mailer 3-47
 - adding a tag to a letter 3-58
 - closing and deleting a letter 3-60, 3-62
 - forwarding a letter 3-50
 - removing a mailer 3-62
 - replying to a letter 3-52
 - when to enable and disable items for mailers 3-31
- 'mail' message family type 7-35
- MailSegmentType data type 3-86
- MailTime data type 3-112
- main aspects
 - defined 5-18
 - for attributes 5-20
 - for records 5-19
- main aspect templates 5-88 to 5-98
 - attribute sample code 5-52 to 5-58
 - custom information page sample code 5-58 to 5-65
 - for attributes 5-22
 - for records 5-21
 - help balloons 5-93, 5-94
 - record sample code 5-30 to 5-33
 - resources used by 5-89 to 5-98
 - specifying attribute category 5-91
 - specifying attribute external category 5-92
 - specifying attribute kind 5-91
 - specifying record category 5-91
 - specifying record external category 5-92
 - specifying record kind 5-91
- main enclosures
 - adding to a letter 3-90
 - defined 3-7
 - getting 3-103
- main view aspect 5-20, 5-136
- master name 166
- matching criteria types 195
- menu commands
 - Add Mailer (Mail menu) 3-47
 - Close and Delete (File menu) 3-60, 3-62
 - Forward (Mail menu) 3-50
 - Lock Key Chain (Special menu) 9-431
 - New (Catalogs menu) 5-94
 - Open (File menu) 3-95
 - Remove Mailer (Mail menu) 3-62
 - Reply (Mail menu) 3-52
 - Reply to All (Mail menu) 3-52
 - Save (File menu) 3-80
 - Tag (Mail menu) 3-58
 - Undo (Edit menu) 3-33, 3-70
 - Unlock Key Chain (Special menu) 9-433
- menus
 - Catalogs menu. *See* Catalogs menu
 - implementing for the Find panel 4-79
 - Mail menu. *See* Mail menu
 - Special. *See* Special menu
 - View menu. *See* View menu
- Menu view type 5-129, 5-162
- message addressing structures 7-24 to 7-26
 - attribute extension type 7-26
 - converting a recipient structure to a byte stream 7-111, 7-115
 - determining size for packed recipient structure 7-108
 - entity name extension 7-26
 - packed recipient structure 7-25
 - packing a recipient structure 7-109
 - queue name extension type 7-26
 - recipient structure 7-24
 - unpacking a packed recipient structure 7-110
 - utility functions 7-107 to 7-114
- message blocks
 - current 7-62
 - getting type and index 7-96
 - nested message 7-59 to 7-61
 - nesting 7-56 to 7-59
 - reading data 7-98 to 7-101
 - starting 7-53 to 7-55
 - TOC in message header 7-7
 - writing data to 7-61 to 7-65
- message family 7-7, 7-35
- message ID structure 7-32
- message information structure 7-36 to 7-37
- message mark 7-63, 7-100
- message queues
 - closing 7-22
 - context
 - closing 7-22, 7-77
 - creating 7-70
 - defined 7-9
 - creating 7-20
 - defined 1-15
 - deleting messages 7-105 to 7-107
 - described 7-8 to 7-9
 - enumerating 7-80 to 7-82
 - filters
 - changing 7-74
 - filter structure 7-35
 - general description 7-8
 - single filter structure 7-34
 - specifying 7-21
 - filter structures 7-34 to 7-35

- managing 7-20 to 7-22, 7-68 to 7-80
- opening 7-20, 7-72 to 7-74
- physical
 - creating 7-69 to 7-70
 - defined 7-8
 - deleting 7-78
 - enumerating 7-21
- reference number 7-8
- virtual
 - closing 7-76
 - creating 7-21, 7-72 to 7-74
 - defined 7-8
- messages
 - adding a nested message 7-59 to 7-61
 - adding a recipient 7-50 to 7-51
 - adding a reply queue 7-52
 - block index 7-96
 - block type 7-96
 - canceling 7-67
 - closing 7-104 to 7-105
 - closing all messages in a context 7-77
 - creating 7-18 to 7-20, 7-43 to 7-68
 - adding information 7-19
 - initiating 7-18
 - deleting 7-105 to 7-107
 - described 7-4 to 7-7
 - digital signature
 - adding 7-67
 - header field 7-7
 - verifying 7-102 to 7-103
 - duplicate 7-18
 - ending 7-20, 7-65 to 7-68
 - family types 7-35
 - header
 - authentication field 7-7
 - contents of 7-6
 - delivery notification field 7-6
 - digital signature field 7-7
 - fixed header information 7-38
 - information about 7-37 to 7-39, 7-89 to 7-96
 - message family field 7-7
 - priority field 7-6
 - process hint field 7-7
 - recipient location information 7-7
 - recipients field 7-92 to 7-94
 - reply queue field 7-7, 7-95 to 7-96
 - sender field 7-7
 - table of contents 7-7
 - TOC information structure 7-37
 - information about 7-36 to 7-40, 7-87 to 7-98
 - header fields 7-89 to 7-96
 - message in queue 7-87
 - recipients 7-92 to 7-94
 - reply queue 7-95 to 7-96
 - listing 7-80 to 7-82
 - modes for reading 7-100
 - modes for writing 7-63
 - nested
 - defined 7-5
 - number of levels 7-19
 - structure of 7-5
 - opening
 - HFS file 7-84
 - in a message queue 7-82 to 7-84
 - nested message 7-86 to 7-87
 - originator of 7-7
 - priority 7-6, 7-34
 - process hint 7-37
 - queues. *See* message queues
 - reading 7-22 to 7-23, 7-80 to 7-105
 - block type and index 7-96
 - closing 7-104 to 7-105
 - data 7-98 to 7-101
 - digital signatures 7-102 to 7-103
 - header fields 7-89 to 7-96
 - opening a nested message 7-86 to 7-87
 - opening an HFS file 7-84
 - opening the message 7-82 to 7-84
 - recipients 7-92 to 7-94
 - reply queue 7-95 to 7-96
 - recipients 7-92 to 7-94
 - reply queue 7-95 to 7-96
 - report 7-9 to 7-10
 - contents 7-10
 - options 7-9
 - saving 7-47 to 7-68
 - . *See also* letters; mail 7-3
 - sender structure 7-40
 - sending 7-43 to 7-47, 7-50 to 7-68
 - starting a block 7-53 to 7-55
 - starting a message to be saved 7-47 to 7-50
 - starting a message to be sent 7-43 to 7-47
 - starting a nested message block 7-56 to 7-59
 - structure of 7-4 to 7-5
 - writing data 7-61 to 7-65
- message type structure 7-28
- message type values 7-27
- messaging service access modules. *See* MSAMs
- metaproperties 5-86 to 5-87
- mouse-down events
 - in information page custom view 5-194
 - in mailers 3-24
- 'msam' file type 5-73
- MSAMs (messaging service access modules)
 - Direct Dialup 7-3
- multiple aspects and information pages 5-18
- MyCompletion function 9-464
- MyCompletionRoutine function ?? to 309
- MyCompletionRoutine function 7-114, 308 to ??
- MyDrawImage function 3-123

MyDrawImageProc function 3-16
 MyDSSpecStreamer function 2-106
 MyFindPanelBusyProc function 4-95
 MyForEachADAPDirectory function 318
 MyForEachAttributeAccessControl function 321
 MyForEachAttrType function 310
 MyForEachAttrTypeLookup function 313 to 314
 MyForEachAttrValue function 314 to 315
 MyForEachDirectory function 311
 MyForEachDirEnumSpec function 315 to 316
 MyForEachDNodeAccessControl function 319
 MyForEachLookupRecordID function 312
 MyForEachRecordAccessControl function 320
 MyForEachRecordID function 309 to 310
 MyFrontWindowCB function 3-124
 MyNotificationProc function 9-465
 MyPanelBusyProc function 4-94
 MyPrepareMailerForDrawing function 3-122
 MyRecipientStreamer function 7-115
 MySendOptionsFilterProc function 3-125
 MyStatusCallBack function 6-54 to 6-55
 MyValidatePackedPathName function 2-11

N

name
 of alias 5-86
 of attribute 5-86, 5-95
 of record 5-86
 name (of owner or issuer of a certificate) 6-9 to 6-11
 name attribute information structure 6-26 to 6-27
 name attributes (distinguished) 6-9 to 6-11
 Name-Binding Protocol (NBP)
 and IPM addresses 7-12
 name resource for AOCE templates 5-75
 native content
 adding to a letter as a main enclosure 3-90
 adding to a letter as blocks 3-91 to 3-93
 getting information about blocks in a letter 3-104
 getting the main enclosure of letter 3-103
 reading blocks in a letter 3-106
 native format 3-104
 native name 9-458
 NBP. *See* Name-Binding Protocol
 nested letters 3-8, 7-5
 nested messages
 adding a message as a nested message block 7-59 to 7-61
 defined 7-5
 number allowed 7-19
 starting a new block 7-56 to 7-59
 networks

 extracting information about PowerShare catalogs
 on 236 to 237
 finding PowerShare catalogs on 232 to 234
 getting information about PowerShare catalogs
 on 234 to 235
 locating 209 to 210
 NetworkSpec data type 2-23
 new-attribute dialog box 5-94
 'nods' resource type 6-22
 notification queue, local identity
 adding to 9-426
 defined 9-405
 manipulating 9-426 to 9-428
 notification function 9-465
 removing from 9-427
 sample 9-411
 using 9-411 to 9-414
 notification type 7-31
 'nteq' lookup table element 5-112
 number property 5-13
 number property type 5-84

O

object types for drop operations 5-203
 OCEAttributeTypeIndex data type 2-40
 OCECopyCreationID function 2-52
 OCECopyDirDiscriminator function 2-63
 OCECopyLocalRecordID function 2-80
 OCECopyPackedDSSpec function 2-95
 OCECopyPackedPathName function 2-55
 OCECopyPackedRecordID function 2-89
 OCECopyPackedRLI function 2-70
 OCECopyRecordID function 2-86
 OCECopyRLI function 2-67
 OCECopyRString function 2-45
 OCECopyShortRecordID function 2-83
 OCECreatorType data type 3-28, 7-27
 OCECTORString function 2-46
 OCEDNodeNameCount function 2-58
 OCEDuplicateRLI function 2-66
 OCEqualCreationID function 2-52
 OCEqualDirDiscriminator function 2-64
 OCEqualDSSpec function 2-99
 OCEqualLocalRecordID function 2-81
 OCEqualPackedDSSpec function 2-100
 OCEqualPackedPathName function 2-61
 OCEqualPackedRecordID function 2-92
 OCEqualPackedRLI function 2-76
 OCEqualRecordID function 2-87
 OCEqualRLI function 2-68
 OCEqualRString function 2-50
 OCEqualShortRecordID function 2-84

- OCEExtractAlias function 2-78
- OCEGetAccessControlDSSpec function 290
- OCEGetDirectoryRootPackedRLI function 2-78
- OCEGetDSSpecInfo function 2-103
- OCEGetExtensionType function 2-105
- OCEGetIndAttributeType function 2-94
- OCEGetIndRecordType function 2-85
- OCEGetRecipientType function 7-113
- OCEIsNullPackedPathName function 2-56
- OCENewLocalRecordID function 2-79
- OCENewRecordID function 2-86
- OCENewRLI function 2-64
- OCENewShortRecordID function 2-82
- OCENullCID function 2-53
- OCEPackDSSpec function 2-97
- OCEPackedDSSpecSize function 2-96
- OCEPackedPathNameSize function 2-57
- OCEPackedRecipient data type
 - creating from OCERecipient data type 7-109
 - defined 7-25
 - determining size 7-108
 - unpacking 7-110
- OCEPackedRecordIDSize function 2-90
- OCEPackedRLIPartsSize function 2-73
- OCEPackedRLISize function 2-71
- OCEPackPathName function 2-60
- OCEPackRecipient function 7-109
- OCEPackRecordID function 2-90
- OCEPackRLI function 2-71
- OCEPackRLIParts function 2-74
- OCEPathFinderCID function 2-54
- OCEPToRString function 2-47
- OCERecipient data type
 - 'alan' extension type 7-12
 - 'aphn' extension type 7-13
 - converting to a byte stream 7-111, 7-115
 - creating from OCEPackedRecipient data type 7-110
 - defined 7-24
 - described 7-10
 - 'entn' extension type 7-14 to 7-17
 - 'attr' subtype 7-15
 - 'qnam' subtype 7-16
 - getting extension type 7-113
 - illustrated 7-11
 - packing 7-109
 - . *See also* addresses; recipient structure
 - setting extension type 7-112
 - utility functions 7-107 to 7-114
- OCERecipientReport data type 7-33
- OCERecordTypeIndex data type 2-28
- OCERelRString function 2-48
- OCERTOPLString function 2-48
- OCESetCreationIDtoNull function 2-54
- OCESetRecipientType function 7-112

- OCESetupAddDirectoryInfo function 9-460
- OCESetupChangeDirectoryInfo function 9-461
- OCESetupGetDirectoryInfo function 9-458
- OCESetupRemoveDirectoryInfo function 9-462
- OCESizePackedRecipient function 7-108
- OCEStreamPackedDSSpec function 2-105
- OCEStreamRecipient function 7-111
- OCEUnpackDSSpec function 2-98
- OCEUnpackPathName function 2-58
- OCEUnpackRecipient function 7-110
- OCEUnpackRecordID function 2-91
- OCEUnpackRLI function 2-72
- OCEValidPackedDSSpec function 2-102
- OCEValidPackedPathName function 2-62
- OCEValidPackedRecordID function 2-93
- OCEValidPackedRLI function 2-77
- OCEValidRLI function 2-69
- OCEValidRString function 2-51
- Open Documents event
 - opening a letter 3-17
- owner requestors 170

P

- 'pabt' file type 4-86
- packed catalog services specifications
 - checking equality of 2-100
 - computing size of 2-96
 - copying 2-95
 - data type defined 2-37
 - minimum-sized 2-38
 - unpacking 2-6 to 2-10, 2-98
 - validating 2-102
- PackedDSSpec data type
 - checking equality of 2-100
 - computing size of 2-96
 - copying 2-95
 - defined 2-37
 - unpacking 2-6 to 2-10, 2-98
 - validating 2-102
- PackedPathName data type
 - checking equality of 2-61
 - computing size of 2-57
 - copying 2-55
 - defined 2-29, 4-23
 - determining number of catalog node names in 2-58
 - determining number of RString structures in 2-58
 - evaluating as null 2-56
 - packing 2-60
 - unpacking 2-58
 - validating 2-62
- packed pathnames 2-29 to 2-30
 - manipulating 2-55 to 2-63

- unpacking 2-29
- packed pathname structure 4-23
 - . *See also* PackedPathName data type 4-23
- packed recipient structure
 - creating from recipient structure 7-109
 - defined 7-25
 - determining size 7-108
 - unpacking 7-110
- PackedRecordID data type
 - checking equality of 2-92
 - computing size of 2-90
 - copying 2-89
 - defined 2-35
 - unpacking 2-91
 - validating 2-93
- packed record identifiers
 - checking equality of 2-92
 - computing size of 2-90
 - copying 2-89
 - data type defined 2-35
 - manipulating 2-88 to 2-94
 - unpacking 2-91
 - validating 2-93
- packed record location information
 - checking equality of 2-76
 - computing size of 2-71, 2-73
 - copying 2-70
 - data type defined 2-33
 - extracting an alias from 2-78
 - getting for personal catalogs 244 to 246
 - minimum-sized 2-33
 - unpacking 2-72
 - validating 2-77
- PackedRLI
 - getting for personal catalogs ?? to 246
- PackedRLI data type
 - checking equality of 2-76
 - computing size of 2-71, 2-73
 - copying 2-70
 - defined 2-33
 - extracting an alias from 2-78
 - unpacking 2-72
 - validating 2-77
- PackedRLI data type
 - getting for personal catalogs 244 to ??
- packed RString list 4-23
- PackedRStringListHandle data type 4-23
- packing
 - AOCE data structures 2-5 to 2-10
 - catalog services specification 2-97
 - DSSpec 2-97
 - PackedPathName 2-60
 - RecordID 2-90
 - record identifiers 2-90
 - record location information 2-71, 2-74
 - RLI 2-71, 2-74
 - 'padz' lookup table element 5-111
 - page-selection pop-up menu 5-97, 5-137
 - panel-busy callback function
 - for Catalog-Browsing panel 4-94
 - for Find panel 4-95
 - installing for Catalog-Browsing panel 4-35
 - installing for Find panel 4-65
 - PanelBusyProc function 4-94
 - panels. *See* Catalog-Browsing panel; Find panel; Personal-Catalog panel 4-29
 - 'panl' resource type 4-34
 - parameter block header 190 to 192
 - parent aspect target selector 5-144
 - parse functions
 - and callback routines and 168
 - using to retrieve access control information 172
 - parsing attributes 5-25
 - . *See also* lookup table
 - partial pathnames 163
 - Pascal strings
 - converting RString to 2-48
 - converting to RString 2-47
 - password
 - adding to PowerTalk Setup catalog 9-460
 - changing for local identity 9-429
 - changing in the PowerTalk Setup catalog 9-461
 - for local identity 9-428
 - Key Chain Access Code 4-6
 - PowerTalk Setup catalog use of 166
 - prompting the user for 6-32 to 6-33
 - removing from PowerTalk Setup catalog 9-462
 - . *See also* authentication; Authentication manager
 - translating into a client key 9-417
 - pasting text
 - AOCE template code resource routine 5-164
 - PathFinder creation ID 2-54
 - pathnames, AOCE
 - defined 2-29 to 2-30, 163
 - getting for dNodes 223 to 225
 - manipulating 2-55 to 2-63
 - packing 2-29
 - using to get dNode numbers 225 to 227
 - pattern-based attribute parsing. *See* lookup table
 - Personal-Catalog panel
 - creating 4-31, 4-34
 - defined 4-9
 - opening the alias of a container 4-60
 - selecting the alias of a container 4-53
 - personal catalog reference number 162
 - personal catalogs
 - closing 243 to 244
 - creating 240 to 241
 - defined 162
 - error when opening 4-28

- expanding group addresses 3-44
- getting packed record location information 244 to 246
- listing access privileges to 242 to 243
- listing features supported 242 to 243
- manipulating 240 to 246
- opening 242 to 243
- sorting 4-28
- physical queues. *See* physical *under* message queues
- picture segments, in letters 3-87
- picture view type 5-130
- pop-up menus
 - AOCE templates
 - adding an item 5-238
 - callback routines 5-238 to 5-242
 - page selection 5-97, 5-137
 - removing an item 5-240
 - returning text of a menu item 5-241
 - view type 5-129
 - Catalog-Browsing panel
 - getting pathname of item 4-40 to 4-42
 - getting size of pathname of item 4-39
- PowerShare catalogs
 - adding to PowerTalk Setup catalog 229 to 234
 - defined 162
 - extracting information about 236 to 237
 - getting information about 234 to 235
 - making available for use 229 to 234
 - removing from PowerTalk Setup catalog 237 to 239
 - . *See also* catalogs 234
- PowerShare collaboration servers xix
- PowerTalk xix
 - . *See also* AOCE
- PowerTalk built-in templates A-1 to A-4
 - address A-4
 - Group records A-4
 - Key Chain A-4
 - User records A-1 to A-3
- PowerTalk Extension file 5-12
- PowerTalk Setup catalog
 - adding catalogs to 229 to 231, 232 to 234
 - defined 166
 - extracting information from catalogs in 199 to 201
 - getting information about catalogs in 196 to 199
 - getting reference number for 239 to 240
 - maintaining 229 to 240
 - master name for 166
 - password for 166
 - removing catalogs from 237 to 239
- PowerTalk system software xix
- PrepareMailerForDrawing function 3-122
- priority of messages 7-6, 7-34
- private-key encryption 6-4
- private keys 6-4
- processes
 - switching between 5-199 to 5-200
- process hint 7-7
- process hint, for message 7-37
- prompt for identity 4-6 to 4-8
- prompt-for-identity dialog box
 - version number 4-5
- properties 5-84 to 5-87
 - and aspect templates 5-13
- AOCE template callback routines
 - getting information 5-213 to 5-222
 - getting property-changed flag 5-221
 - getting property-editable flag 5-222
 - getting size of a binary property 5-219
 - getting types 5-215
 - getting value as a binary block 5-220
 - getting value as an RString 5-217
 - getting value as a number 5-216
 - parsing an attribute value 5-224
 - saving values 5-234
 - setting information 5-223 to 5-235
 - setting property-changed flag 5-231
 - setting property-editable flag 5-232
 - setting property type 5-226
 - setting value as a binary block 5-229
 - setting value as an RString 5-228
 - setting value as a number 5-227
 - type conversions 5-214, 5-223
- changed value callback routine 5-233
- changed value code resource routine 5-167
- converting into attribute values. *See* lookup table
- creating from attribute values. *See* lookup table
- custom type conversions 5-188 to 5-192
 - convert from number 5-191
 - convert from RString 5-192
 - convert to number 5-188
 - convert to RString 5-189
- kDETPPrName metaproperty 5-95
- name of attribute value 5-95
- number range of 5-103
- saving values 5-168, 5-234
- synchronizing values 5-28, 5-185 to 5-187, 5-237
- template-provided routines
 - setting attribute values from properties 5-184
 - setting properties from attribute values 5-182
- types 5-13
- updating values 5-168, 5-185 to 5-187, 5-237
- using resources to set values 5-103
- property-changed flag
 - getting 5-221
 - setting 5-231
- property commands 5-159 to 5-163
 - button 5-161
 - callback routine 5-163
 - checkbox 5-161
 - drop operations 5-162

- pop-up menu 5-162
- radio button 5-161
- sending 5-245
- sorting sublists 5-128
- static command text 5-162
- when the template's property routine is called 5-160
- property-editable flag
 - getting 5-222
 - setting 5-232
- property numbers
 - and property categories 5-85
 - and resource IDs 5-103
 - of an edit-text view 5-211
- property routines, AOCE template 5-158 to 5-169
- property types 5-84
 - assigning in lookup table 5-119
 - constant properties 5-86
 - conversions 5-188 to 5-192, 5-214, 5-223
 - getting information about 5-215
 - local properties 5-85
 - metaproperties 5-86 to 5-87
 - setting 5-226
- property values
 - getting as a binary block 5-220
 - getting as an RString 5-217
 - getting as a number 5-216
 - getting size of a binary property 5-219
 - saving 5-168, 5-234
 - setting as a binary block 5-229
 - setting as an RString 5-228
 - setting as a number 5-227
 - synchronizing 5-28, 5-185 to 5-187, 5-237
 - type conversions 5-188 to 5-192
- 'prop' lookup table element 5-118
- ProtoPackedDSSpec data type 2-38
- ProtoPackedPathname data type 2-30
- ProtoPackedRLI data type 2-33
- ProtoRString data type 2-22
- proxy
 - creating 9-441
 - defined 9-406
 - trading for credentials 9-443
 - using 9-410
- pseudonyms
 - adding to a record 256 to 258
 - defined 165
 - deleting 249 to 250
 - deleting from a record 258 to 259
 - displayed in Catalog-Browsing panel 4-31
 - extracting information about 220 to 221, 262 to 264
 - extracting information from 204 to 206
 - getting information about 201 to 204, 215 to 219, 259 to 262
- 'pstr' lookup table element 5-111
- public-key certificates

- contents of 6-8 to 6-11
- defined 6-6
- getting information from 6-19 to 6-22, 6-45 to 6-54
- identity of owner or issuer 6-8
- range of valid dates 6-8
- signed 6-6
- public key cryptography 6-4
- public keys 6-4, 6-8

Q

- 'qnam' address extension subtype 7-16
- queue context
 - closing 7-22, 7-77
 - creating 7-70
 - defined 7-9
- queue filter structure 7-35
- queue name attribute values for indirect
 - addressing 7-16
- queue name extension structure 7-26
- queue reference number 7-8
- queues
 - messaging. *See* message queues
 - notification. *See* notification queue, local identity
 - reply. *See* reply queue
- QuickTime movie segments
 - adding to a letter 3-87

R

- RadioButton view type 5-129, 5-161
- RC4Key data type 9-416
- 'rcrd' file type 4-86
- reading messages 7-22 to 7-23, 7-80 to 7-105
 - block type and index 7-96
 - closing 7-104 to 7-105
 - data 7-98 to 7-101
 - header fields 7-89 to 7-96
 - opening a nested message 7-86 to 7-87
 - opening an HFS file 7-84
 - opening the message 7-82 to 7-84
 - recipients 7-92 to 7-94
 - reply queue 7-95 to 7-96
 - verifying a digital signature 7-102 to 7-103
- receiving mail 3-17 to 3-19
 - Apple event handler 3-17
 - opening a letter 3-18
- recipient descriptor 3-25
- recipient report messages. *See* report messages
- recipient report structure 7-33
- recipients

- adding to a message 7-50 to 7-51
- authentication process 9-410
- expanding group addresses 3-44
- index 7-33
- location information in message header 7-7
- reading 7-92 to 7-94
- Recipients field of a mailer
 - adding an address 3-118
 - getting 3-113 to 3-115
- RecipientStreamer function 7-115
- recipient structure
 - converting to a byte stream 7-111, 7-115
 - creating from packed recipient structure 7-110
 - defined 7-24
 - described 7-10
 - determining buffer size for packing 7-108
 - getting extension type 7-113
 - illustrated 7-11
 - packed 7-25
 - packing 7-109
 - . *See also* addresses; OCERecipient data type
 - setting extension type 7-112
 - utility functions 7-107 to 7-114
- record alias 165
- record creation IDs 2-26 to 2-27
 - defined 165
- record ID 2-25 to 2-36
 - allocating a maximum-sized structure 2-16 to 2-19
 - binding to a specific identity 9-435
 - checking equality of 2-87
 - copying 2-86
 - creating 2-86
 - defined 2-34, 164 to 165
 - getting for a specific identity 9-438
 - manipulating 2-85 to 2-88
 - of a catalog in the PowerTalk Setup catalog 9-458
 - of authentication initiator 9-455
 - packed 2-35
 - packing 2-90
 - short 2-35
 - unbinding from a specific identity 9-437
- RecordID data type
 - allocating a maximum-sized structure 2-16 to 2-19
 - checking equality of 2-87
 - copying 2-86
 - creating 2-86
 - defined 2-34
 - packing 2-90
- record identifiers. *See* record ID
- record location information
 - checking equality of 2-68
 - copying 2-67
 - creating 2-64
 - defined 2-32, 165
 - duplicating 2-66
 - manipulating 2-64 to 2-79
 - packed 2-33
 - packed minimum-sized 2-33
 - packing 2-71, 2-74
 - unpacking 2-72
 - validating 2-69
- record names
 - changing 254 to 255
 - getting from creation ID 252 to 253
 - new 5-95
- records
 - adding 5-94, 247 to 249
 - adding attribute values to 267 to 268
 - adding pseudonyms to 256 to 258
 - aspect template sample 5-33 to 5-36
 - browsing 4-3
 - categories
 - dropped on other records 5-100
 - listing 4-91
 - listing record types 4-92
 - specifying in an aspect template 5-91
 - changing attribute values in 270 to 272
 - changing name and type 254 to 255
 - creating an aspect from 5-16
 - creation IDs
 - getting 9-446 to 9-448
 - deleting 249 to 250
 - deleting attribute types from 284 to 285
 - deleting attribute values from 269 to 270
 - deleting pseudonyms from 258 to 259
 - determining change in 250 to 252
 - dropping on another record 5-99
 - external category, specifying in an aspect template 5-92
 - extracting access control information for 298 to 301
 - extracting attribute types of 288 to 289
 - extracting attribute values of 280 to 283
 - extracting information about 220 to 221
 - extracting information about pseudonyms 262 to 264
 - extracting information from 204 to 206
 - finding 4-3
 - finding attribute values in 274 to 276
 - gender, of alias 5-94
 - getting access control information for 296 to 298
 - getting attribute types of 285 to 287
 - getting attribute values of 276 to 279
 - getting information about 201 to 204, 215 to 219
 - getting information about pseudonyms 259 to 262
 - getting name and type from creation ID 252 to 253
 - icons for 4-88
 - identifying selection in Catalog-Browsing panel 4-58
 - information page for 5-24
 - kind
 - gender 5-93
 - of alias 5-93

- specifying in an aspect template 5-91
- main aspect 5-19
- main aspect template for 5-21
- main aspect template sample 5-30 to 5-33
- managing 247 to 266
- name 5-86
- name of new 5-95
- new item routine for AOCE templates 5-153
- obtaining dNode numbers 9-446
- obtaining icons for 4-88
- opening selection in Catalog-Browsing panel 4-59
- relation to aspects and AOCE templates 5-11
- specifying AOCE templates for use with 5-139, 5-155
- types displayed in Catalog-Browsing panel 4-32
- types. *See* record types
- verifying attribute values in 272 to 273
- records, AOCE catalog. *See* records
- record-type AOCE template resource 5-75, 5-76
- record types
 - changing 254 to 255
 - defined 165
 - displayed in Catalog-Browsing panel 4-31
 - for AOCE templates 5-75 to 5-77
 - getting from creation ID 252 to 253
 - list of standard 2-28
 - obtaining standard 2-85
- reference number, message queue 7-8
- reference value, custom view 5-242
- Regarding field. *See* Subject field of a mailer
- repeat patterns in lookup tables 5-115
- reply, authentication 9-403
- reply queue
 - adding to a message 7-52
 - defined 7-7
- report block header structure 7-33
- report messages 7-9 to 7-10
 - contents 7-10
 - options for 7-9
- reports
 - delivery notification structures 7-28 to 7-34
 - delivery result 7-33
 - message header delivery notification field 7-6
 - nondelivery codes 7-29 to 7-30
 - notification types 7-31 to 7-32
 - recipient index 7-33
 - recipient report 7-33
 - report block header 7-33
- requestors 170 to 171
 - authenticated in catalog 170
 - authenticated in dNode 170
 - friend 170
 - guest 170
 - owner 170
- resolving aliases of AOCE catalog objects 4-85 to 4-88
 - catalog specification structure 4-87
 - HFS aliases 4-85
- resource ID offsets
 - AOCE templates
 - kDETAAspectAliasGender 5-94
 - kDETAAspectAliasKind 5-93
 - kDETAAspectAliasWhatIs 5-94
 - kDETAAspectAttrDragIn 5-100
 - kDETAAspectBalloons 5-105
 - kDETAAspectCategory 5-91
 - kDETAAspectDragInString 5-101
 - kDETAAspectDragInSummary 5-102
 - kDETAAspectDragInVerb 5-101
 - kDETAAspectDragOut 5-102
 - kDETAAspectExternalCategory 5-92
 - kDETAAspectGender 5-93
 - kDETAAspectInfoPageCustomWindow 5-97
 - kDETAAspectKind 5-91
 - kDETAAspectLookup 5-108 to 5-119
 - kDETAAspectMainBitmap 5-90
 - kDETAAspectName 5-95
 - kDETAAspectNewEntryName 5-95
 - kDETAAspectNewMenuName 5-94
 - kDETAAspectNewValue 5-96
 - kDETAAspectRecordCatDragIn 5-99
 - kDETAAspectRecordDragIn 5-99
 - kDETAAspectReverseSort 5-104
 - kDETAAspectSublistOpenOnNew 5-96
 - kDETAAspectViewMenu 5-103
 - kDETAAspectWhatIs 5-93
 - kDETAAttributeType 5-75, 5-76, 5-77
 - kDETAAttributeValueTag 5-77
 - kDETForwarderTemplateName 5-139
 - kDETInfoPageMainViewAspect 5-136
 - kDETInfoPageMenuEntries 5-137
 - kDETInfoPageName 5-137
 - kDETKillerName 5-140
 - kDETRecordType 5-75, 5-76
 - kDETTemplateName 5-75
- resource IDs
 - and property numbers 5-103
 - for AOCE templates 5-75
- resources
 - AOCE templates
 - Add item string
 - (kDETAAspectNewMenuName) 5-94
 - alias kind (kDETAAspectAliasKind) 5-93
 - aspect templates 5-78 to 5-84
 - aspect template signature resource 5-88
 - attribute category (kDETAAspectCategory) 5-91
 - attribute kind (kDETAAspectKind) 5-91
 - attribute-tag (kDETAAttributeValueTag) 5-77
 - attribute-type (kDETAAttributeType) 5-76, 5-77
 - Catalogs menu items
 - (kDETInfoPageMenuEntries) 5-137

- custom information page
 - (kDETApectInfoPageCustomWindow) 5-97
- drag-in attribute types
 - (kDETApectAttrDragIn) 5-100
- drag-in button label
 - (kDETApectDragInVerb) 5-101
- drag-in description string
 - (kDETApectDragInSummary) 5-102
- drag-in prompt string
 - (kDETApectDragInString) 5-101
- drag-in record categories
 - (kDETApectRecordCatDragIn) 5-99
- drag-in record types
 - (kDETApectRecordDragIn) 5-99
- drag-out attribute types
 - (kDETApectDragOut) 5-102
- drop operations 5-98 to 5-102
- dynamic creation of 5-154 to 5-157
- external category
 - (kDETApectExternalCategory) 5-92
- file type template signature resource 5-141
- forwarder template names
 - (kDETForwarderTemplateName) 5-139
- forwarder template signature resource
 - 5-139
- gender of record alias
 - (kDETApectAliasGender) 5-94
- gender of record kind (kDETApectGender) 5-93
- getting a resource handle 5-207
- help-balloon string for aliases
 - (kDETApectAliasWhatIs) 5-94
- help-balloon string for a record or attribute
 - (kDETApectWhatIs) 5-93
- help-balloon string for properties
 - (kDETApectBalloons) 5-105
- icon (kDETApectMainBitmap) 5-90
- information page name
 - (kDETApectInfoPageName) 5-137
- information page template signature
 - resource 5-121
- killer template names (kDETKillerName) 5-140
- killer template signature resource 5-140
- lookup table (kDETApectLookup) 5-108 to 5-119
- main aspect templates 5-89 to 5-98
- main view aspect name
 - (kDETApectInfoPageMainViewAspect) 5-136
- New attribute value
 - (kDETApectNewValue) 5-96
- New attribute value name
 - (kDETApectName) 5-95
- New item string
 - (kDETApectNewMenuName) 5-94
- New record name
 - (kDETApectNewEntryName) 5-95
- open new item
 - (kDETApectSublistOpenOnNew) 5-96
- properties to sort by
 - (kDETApectViewMenu) 5-103
- properties to sort in reverse order
 - (kDETApectReverseSort) 5-104
- record category (kDETApectCategory) 5-91
- record kind (kDETApectKind) 5-91
- record-type (kDETApectRecordType) 5-76
- signature. *See* signature resource 5-88
- substitution of 5-156
- template name (kDETTTemplateName) 5-75
- view list resource 5-123 to 5-130
- resource types
 - 'deta' 5-88
 - 'detb' 5-96, 5-103
 - 'detc' 5-84
 - 'detf' 5-139
 - 'deti' 5-121
 - 'detc' 5-140
 - 'detm' 5-104, 5-137
 - 'detn' 5-77, 5-103
 - 'detp' 5-104
 - 'dett' 5-108
 - 'detv' 5-123 to 5-130
 - 'detw' 5-97
 - 'detx' 5-141
 - 'dsig' 6-22, 6-36
 - 'find' 4-63
 - 'nods' 6-22
 - 'panl' 4-34
 - 'rst#' 5-91
 - 'rstr' 5-75, 5-103
- used by AOCE templates 5-74
- 'rest' lookup table element 5-111
- RLI data type
 - checking equality of 2-68
 - copying 2-67
 - creating 2-64
 - defined 2-32
 - duplicating 2-66
 - packing 2-71, 2-74
 - validating 2-69
- root catalog
 - obtaining 2-78
- routine selectors, AOCE template
 - callback routines
 - kDETCmdAboutToTalk 5-200
 - kDETCmdAddMenu 5-238
 - kDETCmdBeep 5-198
 - kDETCmdBreakAttribute 5-224
 - kDETCmdBusy 5-200
 - kDETCmdChangeCallFors 5-198
 - kDETCmdCloseEdit 5-212
 - kDETCmdDirtyProperty 5-233

- kDETCmdDoPropertyCommand 5-245
- kDETCmdGetCommandItemN 5-202 to 5-205
- kDETCmdGetCommandSelectionCount 5-201
- kDETCmdGetCustomViewBounds 5-244
- kDETCmdGetCustomViewUserReference 5-242
- kDETCmdGetDSSpec 5-209
- kDETCmdGetOpenEdit 5-211
- kDETCmdGetPropertyBinary 5-219
- kDETCmdGetPropertyBinarySize 5-218
- kDETCmdGetPropertyChanged 5-221
- kDETCmdGetPropertyEditable 5-222
- kDETCmdGetPropertyNumber 5-216
- kDETCmdGetPropertyRString 5-217
- kDETCmdGetPropertyType 5-214
- kDETCmdGetResource 5-207
- kDETCmdGetTemplateFSSpec 5-206
- kDETCmdMenuItemRString 5-241
- kDETCmdOpenDSSpec 5-210
- kDETCmdRemoveMenu 5-240
- kDETCmdRequestSync 5-237
- kDETCmdSaveProperty 5-234
- kDETCmdSelectedSublistCount 5-236
- kDETCmdSetPropertyBinary 5-229
- kDETCmdSetPropertyChanged 5-231
- kDETCmdSetPropertyEditable 5-232
- kDETCmdSetPropertyNumber 5-227
- kDETCmdSetPropertyRString 5-228
- kDETCmdSetPropertyType 5-225
- kDETCmdSublistCount 5-235
- kDETCmdTemplateCounts 5-205
- kDETCmdUnloadTemplates 5-208
- template-provided routines
 - kDETCmdAttributeChange 5-178
 - kDETCmdAttributeCreation 5-175
 - kDETCmdAttributeDelete 5-180
 - kDETCmdAttributeNew 5-176
 - kDETCmdConvertFromNumber 5-190
 - kDETCmdConvertFromRString 5-191
 - kDETCmdConvertToNumber 5-188
 - kDETCmdConvertToRString 5-189
 - kDETCmdCustomMenuEnabled 5-194
 - kDETCmdCustomMenuSelected 5-195
 - kDETCmdCustomViewDraw 5-192
 - kDETCmdCustomViewMouseDown 5-193
 - kDETCmdDoSync 5-186
 - kDETCmdDropMeQuery 5-170
 - kDETCmdDropQuery 5-172
 - kDETCmdDynamicForwarders 5-155
 - kDETCmdDynamicResource 5-156
 - kDETCmdExit 5-151
 - kDETCmdIdle 5-157
 - kDETCmdInit 5-150
 - kDETCmdInstanceExit 5-154
 - kDETCmdInstanceInit 5-152
 - kDETCmdItemNew 5-153
 - kDETCmdKeyPress 5-163
 - kDETCmdMaximumTextLength 5-166
 - kDETCmdOpenSelf 5-158
 - kDETCmdPaste 5-164
 - kDETCmdPatternIn 5-182
 - kDETCmdPatternOut 5-184
 - kDETCmdPropertyCommand 5-159
 - kDETCmdPropertyDirtyed 5-167
 - kDETCmdShouldSync 5-185
 - kDETCmdValidateSave 5-168
 - kDETCmdViewListChanged 5-166
- RSA Data Security, Inc. 6-4
- 'rst#' resource type 5-91
- RString32 data type 2-21
- RString64 data type 2-20
- RString data type
 - checking equality of 2-50
 - comparing sort order of 2-48
 - converting Pascal strings to 2-47
 - converting to Pascal strings 2-48
 - defined 2-20
 - determining number in PackedPathName 2-58
 - validating 2-51
- RStringHeader data type 2-19 to 2-20
- RStringKind data type 2-24
- RString list 4-23
- 'rstr' lookup table element 5-111
- 'rstr' resource type 5-75, 5-103

S

sample routines

- DoAddAttributeValue 175
- DoDisplayCertificateInfo 6-20
- DoDisplayCertificateSet 6-20
- DoDisplayCertNameAttribute 6-20
- DoDisplaySignatureInfo 6-20
- DoEnumerateAttributeTypes 178
- DoEnumerateAttributeValues 175
- DoGetDataToProcess 6-15, 6-17
- DoGetExtendedCatalogInfo 182
- DoGetNumSublistItems 5-70
- DoGetPropertyNumber 5-69
- DoIdle 5-70
- DoInitializeASPB 9-411
- DoInstallNotificationProc 9-411
- DoNoteQueue 9-413
- DoProcessAttributeValues 174
- DoProcessExtendedCatalogInfo 182
- DoRetrieveSignature 6-17
- DoSaveSignature 6-15
- DoSetPropertyNumber 5-70
- DoUnpackExtendedCatalogInfo 182

- DoVerifyData 6-17
- MyAddAppleMailContent 3-15
- MyAddLetterBlocks 3-13
- MyAddLetterImage 3-16
- MyAddNativeContent 3-14
- MyAlbumCode 5-68
- MyAllocateMaxRID 2-17 to 2-18
- MyBuildMailerWindow 3-10
- MyCopyingCode 2-14
- MyCreateFindPanel 4-19
- MyCreateNewPanel 4-9
- MyDeallocateMaxRID 2-18 to 2-19
- MyDisplayDataForSelection 4-15
- MyDoActivate 4-17
- MyDoDeactivate 4-17
- MyDrawImageProc 3-16
- MyFindPanelDispose 4-20
- MyGetLocalIdentity 9-412
- MyGetUserIdentity 4-8
- MyHandleActivates 4-17
- MyHandleIdle 4-18
- MyHandleKeyDownsForPanel 4-13
- MyHandleMouseUp 4-12
- MyHandleOpenDoc 3-18
- MyHandleSREvt 4-17
- MyHandleUpdates 4-16
- MyHandleUserSelection 4-15
- MyInitStandardMail 3-9
- MyMailerCutCommand 3-25
- MyMailerEventHandler 3-22
- MyMailerMouseClickedHandler 3-24
- MyNotificationProc 9-412
- MyProcessEvent 4-12
- MyProcessWhatHappened 3-22
- MyTestForStandardCatalog 4-5
- MyTestForStandardMail 3-8
- MyValidatePackedPathName 2-11
- SAMs (service access modules) 1-14
- saving a message
 - adding a digital signature 7-67
 - adding a nested message 7-59 to 7-61
 - adding a recipient 7-50 to 7-51
 - adding a reply queue 7-52
 - canceling 7-67
 - ending 7-65 to 7-68
 - starting 7-47 to 7-50
 - starting a block 7-53 to 7-55
 - starting a nested message block 7-56 to 7-59
 - writing data 7-61 to 7-65
- script code 2-19
- script structures 194
- script systems
 - sorting a personal catalog 4-28
- SDPDisposeFindPanel function 4-75
- SDPDisposePanel function 4-50
- SDPEnableFindPanel function 4-69
- SDPEnablePanel function 4-45
- SDPFindPanelEvent function 4-76 to 4-78
- SDPFindPanelFocus data type 4-71
- SDPFindPanelRecord data type 4-22
- SDPFindPanelResult data type 4-77
- SDPFindPanelState data type 4-79
- SDPGetCategories function 4-91
- SDPGetCategoryTypes function 4-92
- SDPGetDSSpecIcon function 4-90
- SDPGetFindPanelSelection function 4-82
- SDPGetFindPanelSelectionSize function 4-80
- SDPGetFindPanelState function 4-79 to 4-80
- SDPGetIconByType function 4-88
- SDPGetNewPanel function 4-34 to 4-35
- SDPGetPanelSelection function 4-58
- SDPGetPanelSelectionSize function 4-57
- SDPGetPanelSelectionState function 4-55 to 4-56
- SDPGetPath function 4-40 to 4-42
- SDPGetPathLength function 4-39
- SDPHideFindPanel function 4-67
- SDPHidePanel function 4-43
- SDPInstallFindPanelBusyProc function 4-65
- SDPInstallPanelBusyProc function 4-35
- SDPMoveFindPanel function 4-74
- SDPMovePanel function 4-48
- SDPNewFindPanel function 4-61 to 4-65
- SDPNewPanel function 4-30 to 4-33
- SDPOpenSelectedItem function 4-59 to 4-61
- SDPPanelEvent function 4-52 to 4-54
- SDPPanelRecord data type 4-21
- SDPPromptForID function 4-25 to 4-28
- SDPRepairPersonalDirectory function 4-28
- SDPResolveAliasDSSpec function 4-87
- SDPResolveAliasFile function 4-85
- SDPSelectString function 4-42
- SDPSetFindIdentity function 4-71
- SDPSetFindPanelBalloonHelp function 4-66
- SDPSetFindPanelFocus function 4-70
- SDPSetFocus function 4-46
- SDPSetIdentity function 4-37
- SDPSetPanelBalloonHelp function 4-36
- SDPSetPath function 4-38
- SDPShowFindPanel function 4-68
- SDPShowPanel function 4-44
- SDPSizePanel function 4-49
- SDPStartFind function 4-83
- SDPStopFind function 4-84
- SDPUpdateFindPanel function 4-72 to 4-73
- SDPUpdatePanel function 4-47
- search strings
 - matching criteria 195
- secret key cryptography 6-4
- selection
 - in Catalog-Browsing panel 4-55 to 4-59

- in Find panel 4-79 to 4-83
- SendDateTime field. *See* Sent field of a mailer
- sender structure 7-39
- send-format structure 3-34
- sending a message
 - adding a digital signature 7-67
 - adding a nested message 7-59 to 7-61
 - adding a recipient 7-50 to 7-51
 - adding a reply queue 7-52
 - canceling 7-67
 - ending 7-65 to 7-68
 - starting 7-43 to 7-47
 - starting a block 7-53 to 7-55
 - starting a nested message block 7-56 to 7-59
 - writing data 7-61 to 7-65
- sending mail 3-11 to 3-16, 3-72 to 3-93
 - adding image content 3-16
 - adding letter content 3-13
 - adding native-format content 3-14
 - adding standard-interchange-format content 3-15
 - beginning 3-81 to 3-83
 - ending 3-84
 - extending the send-options dialog box 3-125
 - main routine 3-12
 - send-options dialog box 3-73 to 3-76
- send-letter functions 3-37 to 3-45
 - defined 3-3
- send-options dialog box 3-73 to 3-76
 - displaying 3-11
 - extending 3-125
- SendOptionsFilterProc function 3-125
- send-options structure 3-34
- Sent field of a mailer 3-111
- serial number (of a certificate) 6-8, 6-50
- servers
 - PowerShare 162
- service access modules. *See* SAMs
- session key
 - defined 9-400
 - extracting from credentials 9-455
- Setup catalog
 - adding a catalog and password 9-460
 - changing a record ID and password for a catalog 9-461
 - getting record ID and native name of a catalog 9-458
 - getting reference number of 239
 - manipulating 9-457 to 9-464
 - removing a catalog 9-462
- ShortRecordID data type
 - checking equality of 2-84
 - copying 2-83
 - creating 2-82
 - defined 2-35
- short record identifiers
 - checking equality of 2-84
 - copying 2-83
 - creating 2-82
 - data type defined 2-35
 - manipulating 2-82 to 2-85
- SIGCertInfo data type 6-25
- SIGDigest function 6-44 to 6-45
- SIGDigestPrepare function 6-43 to 6-44
- SIGDisposeContext function 6-29
- SIGFileIsSigned function 6-45 to 6-46
- SIGGetCertInfo function 6-49 to 6-51
- SIGGetCertIssuerNameAttributes function 6-52 to 6-54
- SIGGetCertNameAttributes function 6-51 to 6-52
- SIGGetSignerInfo function 6-48 to 6-49
- SIGNameAttributesInfo data type 6-26 to 6-27
- SIGNameAttributeType data type 6-27
- signature resource
 - aspect templates 5-88
 - defined 5-12
 - file type templates 5-141
 - forwarder templates 5-139
 - information page templates 5-121 to 5-123
 - killer templates 5-140
- signed certificates 6-6, 6-9
- signed digests. *See* encrypted digests
- signer file, prompting the user for 6-32
- signer information structure 6-23 to 6-24
- signer of documents 6-23 to 6-24
 - getting information about 6-48
 - . *See also* digital signatures
- SIGNewContext function 6-28 to 6-29
- signing a file 6-8, 6-22
- SIGProcessData function 6-30 to 6-31
- SIGShowSigner function 6-46 to 6-48
- SIGSignerInfo structure 6-23 to 6-24
- SIGSignFile function 6-36 to 6-38
- SIGSign function 6-34 to 6-35
- SIGSignPrepare function 6-31 to 6-34
- SIGVerifyFile function 6-41 to 6-42
- SIGVerify function 6-40 to 6-41
- SIGVerifyPrepare function 6-38 to 6-40
- single filter structure 7-34
- SLRV data type 194
- SMPAddAddress function 3-118
- SMPAddAttachment function 3-119
- SMPAddBlock function 3-91 to 3-93
- SMPAddContent function 3-85 to 3-88
- SMPAddMainEnclosure function 3-90
- SMPAttachDialog function 3-120 to 3-122
- SMPBecomeTarget function 3-54 to 3-56
- SMPBeginSave function 3-77 to 3-80
- SMPBeginSend function 3-81 to 3-83
- SMPClearUndo function 3-70
- SMPCloseOptions data type 3-30
- SMPCloseOptionsDialog function 3-29, 3-60 to 3-61

- SMPContentChanged function 3-76
- SMPDisposeMailer function 3-29, 3-61
- SMPDrawMailer function 3-72
- SMPDrawNthCoverPage function 3-108
- SMPEnclosureDescriptor data type 3-26
- SMPEndSave function 3-80
- SMPEndSend function 3-84
- SMPEnumerateBlocks function 3-104
- SMPExpandOrContract function 3-56
- SMPGetComponentInfo function 3-111 to 3-113
- SMPGetComponentSize function 3-110
- SMPGetDimensions function 3-48
- SMPGetFontNameFromLetter function 3-102
- SMPGetLetterInfo function 3-27, 3-93
- SMPGetListItemInfo function 3-113 to 3-115
- SMPGetMailerState function 3-30, 3-69
- SMPGetMainEnclosureFSSpec function 3-103
- SMPGetNextLetter function 3-27, 3-97
- SMPGetTabInfo function 3-53
- SMPImageErr function 3-42
- SMPImage function 3-88 to 3-89
- SMPInitMailer function 3-46
 - using 3-9
- SMPLetterInfo data type 3-27
- SMPLetterPB parameter block 3-29
- SMPMailerEditCommand function 3-67
- SMPMailerEvent function 3-63 to 3-67
- SMPMailerForward function 3-49 to 3-51
- SMPMailerReply function 3-51 to 3-53
- SMPMailerState data type 3-30 to 3-34
- SMPMoveMailer function 3-57
- SMPNewMailer function 3-46 to 3-48
- SMPNewPage function 3-41
- SMPOpenLetter function 3-27, 3-94 to 3-96
- SMPPrepareCoverPages function 3-107
- SMPPrepareToChange function 3-83
- SMPPrepareToClose function 3-59
- SMPReadBlock function 3-106
- SMPReadContent function 3-98 to 3-102
- SMPRecipientDescriptor data type 3-25
- SMPResolveToRecipient function 3-25, 3-44
- SMPSendFormat data type 3-35
- SMPSendLetter function 3-25, 3-26, 3-29, 3-37 to 3-41
- SMPSendOptions data type 3-34
- SMPSendOptionsDialog function 3-34, 3-73 to 3-76
- SMPSetFromIdentity function 3-117
- SMPSetSubject function 3-116
- SMPTagDialog function 3-58
- snapshot. *See* image content
- sound segments, in letters 3-87
- Special menu
 - locking local identity 9-431
 - unlocking local identity 9-433
- specific identity
 - binding 9-435
 - creating 9-435
 - defined 4-6, 166, 9-405
 - for Catalog-Browsing panel 4-37
 - for Find panel 4-71
 - getting record ID 9-438
 - introduction 1-18
 - management 9-435 to 9-439
 - prompting for 4-25 to 4-28
 - removing 9-437
- spinning cursor 4-95
- stand-alone attribute 5-6
- Standard Catalog Package 4-3 to 4-115
 - application-defined functions for 4-94 to 4-95
 - data structures for 4-20 to 4-23
 - functions in 4-23 to 4-93
 - authenticating a user 4-25 to 4-28
 - calling from assembly language 4-24
 - creating, displaying, and disposing of a Catalog-Browsing panel 4-29 to 4-51
 - creating, displaying, and disposing of a Find panel 4-61 to 4-75
 - handling Catalog-Browsing panel events 4-51 to 4-61
 - handling find-panel events 4-75 to 4-85
 - obtaining icons and lists of catalog-item categories and types 4-88 to 4-93
 - resolving aliases 4-85 to 4-88
 - sorting a personal catalog 4-28
 - introduction 1-12
 - testing for availability 4-5
 - version number 4-5
- standard interchange format
 - adding to a letter 3-15, 3-85 to 3-88
 - converting font numbers to font names 3-102
 - defined 3-7
 - reading 3-98 to 3-102
- Standard Mail Package 3-3 to 3-153
 - application-defined functions for 3-122 to 3-126
 - data structures for 3-25 to 3-35
 - functions in 3-36 to 3-122
 - calling from assembly language 3-36
 - getting and setting information in a mailer 3-110 to 3-122
 - handling events in mailers 3-63 to 3-72
 - initializing 3-46
 - opening and reading mail 3-93 to 3-107
 - printing and imaging mailers 3-107 to 3-109
 - providing a mailer in your window 3-45 to 3-63
 - sending and saving mail 3-72 to 3-93
 - send-letter functions 3-37 to 3-45
 - initializing 3-8
 - introduction 1-11
 - relationship to Interprogram Messaging Manager 7-3
 - testing for availability 3-8

- version number 3-8
- standard record types
 - list of 2-28
 - obtaining 2-85
- standard signatures
 - adding 6-8, 6-22, 6-36
 - getting information on 6-45 to 6-54
- StaticCommandTextView view type 5-128, 5-162
- StaticTextView view type 5-127
- StaticText view type 5-128
- Stop button, for Find panel 4-80, 4-84
- store-and-forward 1-15
- string property type 5-13, 5-84
 - . *See also* RString data type
- strings. *See* AOCE strings
- styled text, in letters 3-87
- styles
 - constants for view lists 5-127
- 'styp' lookup table element 5-119
- Subject field of a mailer
 - getting 3-111
 - specifying 3-116
- sublist item target selector 5-144
- sublists
 - automatically opening information page for new item 5-96
 - callback routines 5-235 to 5-238
 - determining number of items in sublist 5-235
 - synchronizing with catalog system 5-237
 - example 5-8
 - information page for attribute in 5-23
 - information page for record in 5-24
 - and main aspects 5-22
 - name of attribute value 5-95
 - preventing the user from dragging out attribute values 5-102
 - sample information page 5-43 to 5-52
 - sorting 5-103, 5-104, 5-128, 5-162
 - specifying types of attribute values that can be dragged out 5-102
 - useInSublist lookup-table flag 5-109
 - and view lists 5-136
- synchronizing property values with the catalog system 5-185 to 5-187, 5-237

T

- Tab key
 - selecting Catalog-Browsing panel 4-46
 - selecting Find panel 4-70
 - using to move among fields in a mailer 3-53 to 3-56
- tags

- adding to letters 3-58
- close-options dialog box 3-60
- target components 3-32
- target selectors 5-144
- target specifier structure 5-142 to 5-145
- template name resource 5-75
- template names 5-75
- template resources. *See* resources
- templates. *See* AOCE templates
- template unloader 5-208
- text
 - AOCE template code resource routines 5-164, 5-166
 - as content of a letter 3-87
- text justification. *See* justified text
- text styles. *See* styles
- text views
 - . *See also* edit-text views
 - types of 5-127
- time
 - getting UTC 9-448 to 9-450
- time service 9-448 to 9-450
- TOC information structure 7-37
- To field. *See* Recipients field of a mailer
- TPfPgDir data type 3-28
- type
 - determining for a letter in the In tray 3-94
- type conversions, AOCE template properties 5-188 to 5-192
 - convert from number 5-191
 - convert from RString 5-192
 - convert to number 5-188
 - convert to RString 5-189
 - on requesting a property value 5-214
 - on setting a property value 5-223
- 'type' lookup table element 5-111

U

- Undo command
 - for mailers 3-33, 3-70
- universal coordinated time. *See* UTC
- unpacking
 - AOCE data structures 2-5 to 2-10
 - packed catalog services specifications 2-98
 - PackedDSSpec 2-98
 - PackedPathName 2-58
 - PackedRecordID 2-91
 - packed record identifiers 2-91
 - PackedRLI 2-72
 - record location information 2-72
- update events
 - for Catalog-Browsing panels 4-47
 - for Find panels 4-72 to 4-73

- for mailers 3-72
- useForInput lookup-table flag 5-109
- useForOutput lookup-table flag 5-109
- useInSublist lookup-table flag 5-109
- user names
 - for local identity 9-428
- User record templates A-1 to A-3
- UTC, getting 9-448 to 9-450
- UTCOffset data type 3-112
- UTCTime data type 3-112, 7-33
- utilities. *See* AOCE Utilities
- utility functions. *See* AOCE utility functions

V

- view lists 5-123 to 5-131
 - and sublist sorting 5-128
 - code resource routine 5-166
 - custom view bounds 5-244
 - custom view reference value 5-242
 - flags 5-126
 - font constants 5-127
 - sample 5-130
 - and sublists 5-136
 - text justification constants 5-127
 - text style constants 5-127
 - view types 5-127 to 5-130
- View menu 5-7
 - and sublist sorting 5-103, 5-104
- views
 - conditional
 - code resource routine 5-166
 - defined 5-26
 - implementing 5-131 to 5-136
 - sample 5-40 to 5-43
 - custom
 - callback routines 5-242 to 5-245
 - code resource routines 5-192 to 5-194
 - defined 5-130
 - getting bounds 5-244
 - getting reference value 5-242
 - handling mouse-down event 5-194
 - updating 5-193
- view types 5-127 to 5-130
- virtual queue. *See* virtual *under* message queues
- viruses
 - detecting with digital signatures 6-3
- visitor, PowerTalk. *See* alternate user, PowerTalk

W

- watch cursor
 - disabling 5-200
- windows
 - adding a mailer 3-46
 - information page. *See* custom information page
 - window; information page
 - moving a mailer in 3-57
 - preparing for mailer 3-123
- 'word' lookup table element 5-111
- workflow application example 1-7
- wristwatch cursor
 - disabling 5-200
- 'wsiz' lookup table element 5-115
- 'wstr' lookup table element 5-111

